ALT.NO	ALT.DATE	ZONE	ALTERATIONS	AUTHORITY
9	22/01/2026	ALL	1. BOM UPDATED.	C.R.No. 2300250018

15	2X1.5 SQ.MM. MULTI CORE CABLE 600/1000V(IN MTRS)DATA SHEET-4	250	NIL	EDTS-132,REV-C, AM-3,CORR-1	REFERD IN EDTS-252, REV-J, CORR-9
14	18X1.5 SQ.MM. MULTI CORE CABLE 600/1000V(IN MTRS)DATA SHEET-7	35	NIL	EDTS-132,REV-C, AM-3,CORR-1	REFERD IN EDTS-252, REV-J, CORR-9
13	25X1.5 SQ.MM. MULTI CORE CABLE 600/1000V(IN MTRS)DATA SHEET-7	37	NIL	EDTS-132,REV-C, AM-3,CORR-1	REFERD IN EDTS-252, REV-J, CORR-9
12	(4X4X1)C+2X0.75(18 CORES) MULTI CORE CABLE 600/1000V(IN MTRS)DATA SHEET-5	36	NIL	EDTS-132,REV-C, AM-3,CORR-1	REFERD IN EDTS-252, REV-J, CORR-9
11	4 SQ.MM.(GN/Y)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	35	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
10	4 SQ.MM.(BLUE)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	105	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
9	4 SQ.MM.(YELLOW)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	105	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
8	4 SQ.MM.(RED)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	105	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
7	1.5 SQ.MM.(CHOCO.)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	605	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
6	1.5 SQ.MM.(WHITE)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	482	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
5	1.5 SQ.MM.(GN/Y)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	782	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
4	1.5 SQ.MM.(BLACK)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	844	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
3	1.5 SQ.MM.(BLUE)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	161	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
2	1.5 SQ.MM.(YELLOW)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	182	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9
1	1.5 SQ.MM.(RED)THIN WALLED FLEX. ELAST. CABLE WITH CU. COND., UPTO 750V(IN MTRS.)	636	NIL	ELRS/SPEC/ELC/O 019,REV-4	REFERD IN EDTS-252, REV-J, CORR-9

WELD LENGTH	ITEM	DESCRIPTION & DIMENSIONS	QPASSLY	DETAIL DRG	MATL. & SPEC.	REMARKS
NIL M	GROUP	ELECTRICAL	SUPERSEDES:	LW70203 ALT f		
WEIGHT	FILE	D:\lw70203g.prt (2D)				
NIL KG						
S.AREA						
NIL M^2						
~~LENGTH / DIA~~						
NIL M						
~~WIDTH / THICK~~						
NIL M						
HEIGHT						
NIL M						

HARNESS CHART FOR ROOF

(FOR AC 2-TIER EOG LHB TYPE COACHES)

RAIL COACH FACTORY, KAPURTHALA

रेलकोच फैक्टरी कपूरथला | IRS

SEE/D&D | DY.CEE/D&D

SCALE	SSE/ED		
	CHD		
	DRN	BKRM LOGIN	
REF.DRG.No.	NIL		
PL NO.	NIL		
DRG.NO.	LW70203		
ALT. 9	SIZE A2	SHEET 1/1	

THIS DRAWING IS THE INTELLECTUAL PROPERTY OF RAIL COACH FACTORY, KAPURTHALA.
THIS DRAWING SHALL NOT BE REPRODUCED, ALTERED, USED FOR MANUFACTURING OF COMPONENTS, SOLD OR TRANSFERRED WITHOUT PERMISSION FROM CHIEF DESIGN ENGINEER, RAIL COACH FACTORY, KAPURTHALA.

REFER EDTS-252, REV-J, CORR-9

DETAIL DRGS STARTING WITH "LI" ARE INTERNAL REFERENCE LISTS ONLY AND ARE NOT FOR ISSUE

ANY MANUAL ALTERATION SHALL AUTOMATICALLY RENDER THIS DRAWING INVALID.

FOR UNTOLERANCED DIMENSIONS REFER MDG0008 | DATE OF FIRST ISSUE | 20/12/2025