RAIL COACH FACTORY, KAPURTHALA

MD35131 DATED: 10/03/2026

Sub: - Issue of corrigendum-2 of "TECHNICAL SPECIFICATION FOR FRP COMPONENTS COMPLYING FIRE RETARDANT CHARACTERISTICS AS PER EN 45545-2" MDTS-43373 (Rev-01).

Following modifications are made to the clause 11, table-7(Quality Assurance, Tests & Documents) in specification no. MDTS-43373 Rev-01.

S.No.	Clause	Earlier	Modified
1.	11	In the Point "Routine Tests" of Table -7 following test are given earlier- • Tensile strength (N/MM²)-min • Tensile modulus (N/MM²)-min • % age elongation at break % min • Inter laminar shear strength- min (N/mm²) • Cross breaking strength (N/MM²)-min • Izod strength (joule/mtr.) • Resistance to Impact test	After the modification, the following tests should be considered as routine tests- • Tensile strength (N/MM²)-min • Tensile modulus (N/MM²)-min • % age elongation at break % min • Inter laminar shear strength- min (N/mm²) • Cross breaking strength (N/MM²)-min • Izod strength (joule/mtr.)

Resistance to impact test deleted from routine test.

10/03/26

DY.CME/DF

10/3/26.

CDE/RCF- may kindly approve the same.

Copy for information to:

CME/QA, CDE, CPLE, CWE/FUR, CMM/HSQ, CMT, CWE/SHELL, DY.CME/LHB/HSQ

DY.CMM/G, DY. CPLE-II & III, DY.CMM/FUR, DY.CME/D Vendor, DY.CME/D Shell,

DY.CME/D Bogie

SSE/Record (with original copy), SSE/Filing section, SSE/LIB. Mech. Design,

SSE/Design/RCF/TKJ