

Rail Coach Factory, Kapurthala

MD35131

Dated: 15/10/2024

Sub: Issue of Corrigendum-2 of specification no. MDTs-116 Rev 6 of TECHNICAL SPECIFICATION FOR INSULATING MATERIAL WITH SELF-ADHESIVE FILM.

Clause	Earlier	Modified
S.No. 3 of Table-3 (Technical Properties ) of Para 5.8	Noise Reduction Coefficient- Evaluation standard DIN-52215 and Specified Parameters Value as per Annexure-A	Noise Reduction Coefficient- Evaluation standard DIN-52215 / EN ISO-10534- 2/ASTM E 1050 and Specified Parameters Value as per Annexure-A  Or  Required value of Sound absorption / Noise reduction Coefficient => 0.20 ( for 25 mm) Test method as per AS 1045/ISO 354/EN ISO 11654

  
Dy.CME/FD

CME/QA CPLE CWE/Fur CMM/HSQ CWE/Shell

Dy. CME/LHB/HSQ Dy. CMM/G CMT Dy.CPLE-II & III Dy.CMM/Fur

SSE/Filing Section

SSE/Library, Mech. Design

SSE/Record (Original Copy)

SSE/Dev.

Copy for kind information to:

CDE

Dy. CME/D Vendor/D Shell/D Bogie