

Material List for Flexible Flame-Retardant, High Performance, Polyolefin Heat-Shrinkable Tubing

This material list covers the supply of Flexible flame-retardant, high performance, polyolefin heat-shrinkable tubing for LHB EOG AC Coaches and LHB EOG Non AC Coaches.

SN	Suitable cable size in sq.mm	Suitable crimping socket for cable size	Description	Sleeve Size	Sleeve length	Colour	QPC		
							LHB AC Coaches	LHB Non-AC Coaches except LSLRD	LHB Non-AC LSLRD Coaches
1	150	150	Flexible flame-retardant, high performance, polyolefin heat-shrinkable tubing to Cat. no. RNF-100, Type-1, of M/s Tyco Electronics or Equivalent of M/s Panduit or MV Electro-systems or M/s Phoenix or M/s Novo-flex make.	31.7	2"	Red	8	8	12
2	150	150		31.7	2"	Yellow	8	8	12
3	150	150		31.7	2"	Blue	8	8	12
4	95	95		25.4	2"	Black	8	8	12
5	70	70		19.1	2"	Green	4	4	4
6	50	50		19.1	2"	Red	6	-	-
7	50	50		19.1	2"	Yellow	6	-	-
8	50	50		19.1	2"	Blue	6	-	-
9	50	50		19.1	2"	Black	6	-	-
10	25	25		12.7	2"	Red	2	4	4
11	25	25		12.7	2"	Yellow	2	4	4
12	25	25		12.7	2"	Blue	2	4	4
13	25	25		12.7	2"	Black	2	4	4
14	16	16		9.5	2"	Red	-	4	4
15	16	16		9.5	2"	Yellow	-	4	4
16	16	16		9.5	2"	Blue	-	4	4
17	16	16		9.5	2"	Black	-	4	4
18	6	6		6.4	2"	Red	-	2	2
19	6	6		6.4	2"	Yellow	-	2	2
20	6	6		6.4	2"	Blue	-	2	2
21	6	6		6.4	2"	Black	-	2	2
22	4	4		6.4	2"	Red	2	-	-
23	4	4		6.4	2"	Yellow	2	-	-
24	4	4		6.4	2"	Blue	2	-	-
25	4	4		6.4	2"	Black	2	-	-
26	2.5	2.5		6.4	2"	Red	2	-	-
27	2.5	2.5		6.4	2"	Yellow	2	-	-
28	2.5	2.5		6.4	2"	Blue	2	-	-

EDML-176	Nil	27.03.21				1 of 1
Doc. No.	Rev.	Date	SSE/CAD	SEE/D&D	DY.CEE/D&D	PAGE