

ZS COUPLING FOR LHB COACHESA TECHNICAL DATA

Operating voltage	750 volts \pm 5 %, 3 phase , 50 Hz
Rated current (Main Contacts 4 Nos.)	400 amps
Rated current (control contacts 4 Nos.)	25 Amps
Material	Hard silver on copper
Contact system	Spring pressure contacts mounted in the receptacle
Pressure	68-113 N force
Contact resistance	0.1 m ohms.
Protection	IP65
Connectors in junction box	Wohner/ Klockner Moiler conforming to IEC947 with insulation withstand voltage of 1000 volts and terminations suitable for 95 to 185 mm ² cable

B SCOPE OF SUPPLY

Sr. No.	Description	M/s Fabeg Drawing no	Alt	QPC
1	Terminal box (Model - A)	165.121.010 GZ-1	C	2
2	Terminal box (Model - B)	165.121.011 GZ-1	C	2
3	Socket	165.121.013 GZ-1	D	2
4	Jumper Plug	165.121.012 GZ-1	C	2
5	Blind socket	165.121.014 GZ-1	B	2

EDML010	0	28-Sep-00			1 OF 1
SPEC. NO.	REV.	DATE	UNIT SUPERVISOR	SEE/D&D DYCEE/D&D	SHEET