



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4598	DISPATCH DATE:			09.04.2015
2.	RAILWAY	SWR	Type:	GS	Coach No.:	15402
3.	Booked to	SSE/C&W/SBC				
4.	Tare Weight of Coach :	36.99T				
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			200 mm		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			ATUL		
ix)	Draw Gear (Make)			RK		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123		SATISFACTORY			
8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			OVPL		
iii.	WATER TANKS			RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			TAYAL		
vi.	WINDOWS			AGF,MECIDON		
vii.	LAV. DOORS			DHINJAN		
viii.	LP SHEET			NA		
ix)	BIO- TOILET			M K PRECISION		
10.	10.1	Modification/ Trial (if any):		NIL		
	10.2	Deviations (if any):		NIL		



12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date			
		4598	SWR	GS	15402	25-03-2015			
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'								
12.2	Wheel & Axle Details:	PP Side				NPP Side			
	i. Bogie No.	150327				150326			
	ii. Frame No.	ASR-09				ASR-1059			
	iii. Axle No.	10318		V-9548		10047		A-4428	
	iv. Wheel Diameter	917.00	916.50	916.00	916.00	915.50	916.00	915.00	915.00
	v. Wheel Disc No.	09447/ 13353	05784/ 13736	09014/ 13204	06097/ 13471	06130/ 13470	06066/ 13471	08972/ 13204	06124/13 471
	vi. R.B. Nos.	A-1262	A-1285	A-0408	A-0409	A-1541	A-1358	A-1491	A-1412
	vii. R.B. Make	NBC		NBC		NBC		NBC	
	viii. R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>								
	i.	BRAKE CYLINDER (Make)				PEW,AJT			
	ii.	SECONDARY Shock Absorber (Make)				KNORR BREMSE			
12.4	i.	Modification/ Trail (if any):				NIL			
	ii.	Deviations (if any):				NIL			

GS-4598



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4594	DISPATCH DATE:			10.04.2015
2.	RAILWAY	SWR	Type:	GS	Coach No.:	15404
3.	Booked to	SSE/C&W/SBC				
4.	Tare Weight of Coach :	36.99T				
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			200 mm		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1103	1104/1103	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			RK		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	85/85	
8.2	APPLICATION OF PCN-123		SATISFACTORY			
8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			FAIVELEY		
ii.	SEAT & BERTH			OVPL		
iii.	WATER TANKS			RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			TAYAL		
vi.	WINDOWS			ABC, AGF,MECIDON		
vii.	LAV. DOORS			DHINJAN		
viii.	LP SHEET			NA		
ix)	BIO- TOILET			M K PRECISION		
10.	10.1	Modification/ Trial (if any):		NIL		
	10.2	Deviations (if any):		NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date			
		4594	SWR	GS	15404	26-03-2015			
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'								
12.2	Wheel & Axle Details:	PP Side				NPP Side			
	i. Bogie No.	150332				150333			
	ii. Frame No.	ASR-05				ASR-17			
	iii. Axle No.	RF-105158		A-4180		Y-7648		P-5893	
	iv. Wheel Diameter	915.00	915.00	916.00	916.00	916.00	916.00	916.50	916.00
	v. Wheel Disc No.	06118/ 13471	06133/ 13471	62048/ 09759	62794/ 08675	06007/ 13448	60844/ 08510	05832/ 13808	06401/13 600
	vi. R.B. Nos.	A1477	A1536	M3164	A3171	A1397	A1515	A1366	A1468
	vii. R.B. Make	NBC		NBC		NBC		NBC	
	viii. R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>								
	i.	BRAKE CYLINDER (Make)				AJT			
	ii.	SECONDARY Shock Absorber (Make)				KNORR BREMSE			
12.4	i.	Modification/ Trail (if any):				NIL			
	ii.	Deviations (if any):				NIL			

GS-4594



ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4593	DISPATCH DATE:			10.04.2015
2.	RAILWAY	SWR	Type:	GS	Coach No.:	15405
3.	Booked to	SSE/C&W/SBC				
4.	Tare Weight of Coach :	36.99T				
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
	6.1	Leading Dimensions;				
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)	
	ii)	Maximum length over Body			21337 ± 10	
	iii)	Maximum length over Buffer			22297 ± 15	
	iv)	Maximum width over Body			3245 ± 5	
	v)	Maximum width over Flasher light			3402 +0/-5	
	vi)	Minimum height above rail level to the lowest fitting			200 mm	
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1103	1104/1104
	viii)	Buffer/CBC (Make)				ATUL
	ix)	Draw Gear (Make)				RK
7.	Air Brake Testing:					
		Description			Specified	
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)	
			Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)	
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application	
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"	
	7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"	
	7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)	
8.	PAINTING DEATAILS:					
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE	
	8.1	PAINT	PU PAINT	VIBGYOR	85/86	
	8.2	APPLICATION OF PCN-123			SATISFACTORY	
	8.3	INSUALTION			SATISFACTORY	
9.	Traceability of Furnishing Items:					
	i.	BRAKE EQUIPMENT			Make ESCORTS	
	ii.	SEAT & BERTH			OVPL	
	iii.	WATER TANKS			RAIL FAB	
	iv.	PVC			RESPONSIVE	
	v.	FLOOR BOARD			TAYAL	
	vi.	WINDOWS			ABC,MECIDON	
	vii.	LAV. DOORS			DHINJAN	
	viii.	LP SHEET			NA	
	ix)	BIO- TOILET			M K PRECISION	
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4593	SWR	GS	15405	04-03-2015				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	150259				150262			
	ii.	Frame No.	ASR-969				ASR-1017			
	iii.	Axle No.	U-4976		N-8078		U-9907		S-1543	
	iv.	Wheel Diameter	916.50	917.00	916.50	917.00	916.50	916.50	917.00	916.50
	v.	Wheel Disc No.	10385/252	10179/382	10281/211	10359/262	10312/246	10323/374	10204/382	10329/259
	vi.	R.B. Nos.	J-2164	J-2163	A-1399	A-1508	A-1407	A-0706	J-2351	J-2350
	vii.	R.B. Make	NBC		NBC		NBC		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				PEW				
	ii.	SECONDARY Shock Absorber (Make)				KNORR BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

GS-4593



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4595	DISPATCH DATE:			10.04.2015
2.	RAILWAY	SWR	Type:	GS	Coach No.:	15403
3.	Booked to	SSE/C&W/SBC				
4.	Tare Weight of Coach :	36.99T				
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			200 mm		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1103/1104	
viii)	Buffer/CBC (Make)			ATUL		
ix)	Draw Gear (Make)			RK		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			OVPL		
iii.	WATER TANKS			RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			TAYAL		
vi.	WINDOWS			ABC,AGF, MECIDON		
vii.	LAV. DOORS			DHINJAN		
viii.	LP SHEET			NA		
ix)	BIO- TOILET			M K PRECISION		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4595	SWR	GS	15403	24-03-2015				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	150321				150320			
	ii.	Frame No.	ASR-1082				ASR-07			
	iii.	Axle No.	A-3908		4147		N-7231		9523	
	iv.	Wheel Diameter	916.00	916.00	917.00	917.00	916.00	916.00	916.00	916.00
	v.	Wheel Disc No.	08577/ 13808	06108/ 13471	09676/ 14862	07246/ 13338	09393/ 13353	60839/ 08510	06394/ 13600	09326/13 353
	vi.	R.B. Nos.	A-1194	A-1103	A-1324	A-1411	M-2763	M-2808	M2767	M-2788
	vii.	R.B. Make	NBC		NBC		NBC		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				PEW				
	ii.	SECONDARY Shock Absorber (Make)				KNORR BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

GS-4595



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4591	DISPATCH DATE:			11.04.2015	
2.	RAILWAY	SWR	Type:	GS	Coach No.:	15406	
3.	Booked to	SSE/C&W/SBC					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1103	1104/1104		
viii)	Buffer/CBC (Make)			JLS			
ix)	Draw Gear (Make)			RK			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT		VIBGYOR	85/86		
8.2	APPLICATION OF PCN-123			SATISFACTORY			
8.3	INSUALTION			SATISFACTORY			
9.	Traceability of Furnishing Items:						
i.	BRAKE EQUIPMENT			Make FAIVELEY			
ii.	SEAT & BERTH			MANOJ			
iii.	WATER TANKS			RAIL FAB			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			TAYAL			
vi.	WINDOWS			AGF, MECIDON			
vii.	LAV. DOORS			DHINJAN			
viii.	LP SHEET			NK			
ix)	BIO- TOILET			M K PRECISION			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway		Type	Coach No.		Dispatch Date			
		4591	SWR		GS	15406		26-03-2015			
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
12.2	Wheel & Axle Details:	PP Side					NPP Side				
	i.	Bogie No.	150330					150329			
	ii.	Frame No.	ASR-08					ASR-1023			
	iii.	Axle No.	A-4513		A-4698		A-9403		RWF-91073		
	iv.	Wheel Diameter	917.00	917.00	917.00	917.00	917.00	917.00	917.00	917.00	
	v.	Wheel Disc No.	05159/ 13830	06674/ 13094	06077/ 13471	06171/ 13481	06666/ 13094	06063/ 13471	60826/ 08510	05188/13 830	
	vi.	R.B. Nos.	A1147	A1037	J2144	J2114	J2106	J2112	J2125	J2122	
	vii.	R.B. Make	NBC		NBC		NBC		NBC		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	Items Traceability:										
	i.	BRAKE CYLINDER (Make)					AJT				
	ii.	SECONDARY Shock Absorber (Make)					KNORR BREMSE				
12.4	i.	Modification/ Trail (if any):					NIL				
	ii.	Deviations (if any):					NIL				

GS-4591



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	5004	DISPATCH DATE:			20.04.2015	
2.	RAILWAY	SWR	Type:	GS	Coach No.:	15401	
3.	Booked to	SSE/C&W/SBC					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104		
viii)	Buffer/CBC (Make)			ATUL			
ix)	Draw Gear (Make)			RK			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT		APC	85/86		
8.2	APPLICATION OF PCN-123			SATISFACTORY			
8.3	INSUALTION			SATISFACTORY			
9.	Traceability of Furnishing Items:						
i.	BRAKE EQUIPMENT			Make FAIVELEY			
ii.	SEAT & BERTH			MANOJ			
iii.	WATER TANKS			AMIT			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			TAYAL			
vi.	WINDOWS			AGF, ABC, MECIDON			
vii.	LAV. DOORS			DHINJAN			
viii.	LP SHEET			NA			
ix)	BIO- TOILET			OASIS			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway		Type	Coach No.	Dispatch Date				
		5004	SWR		GS	15401	31-03-2015				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
12.2	Wheel & Axle Details:	PP Side					NPP Side				
	i.	Bogie No.	150349					150347			
	ii.	Frame No.	UBLS-1321					ASR-1034			
	iii.	Axle No.	P-1931		8696		U-6691		A-3948		
	iv.	Wheel Diameter	917.00	916.50	916.00	916.00	917.00	917.00	916.00	916.00	
	v.	Wheel Disc No.	62852/ 08675	05794/ 13808	08843/ 13172	08850/ 13172	05993/ 13448	06462/ 13600	08922/ 13204	06050/13 471	
	vi.	R.B. Nos.	M-3151	M-3179	J-1900	M-0698	J-2313	J-2282	A-0424	A-0404	
	vii.	R.B. Make	NBC		NBC		NBC		NBC		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	Items Traceability:										
	i.	BRAKE CYLINDER (Make)					PEW,AJT				
	ii.	SECONDARY Shock Absorber (Make)					KNORR BREMSE				
12.4	i.	Modification/ Trail (if any):					NIL				
	ii.	Deviations (if any):					NIL				

GS-5004