



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4342	DISPATCH DATE:			10.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143539	
3.	Booked to	SSE/C&W/FZR					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104		
viii)	Buffer/CBC (Make)			REPL			
ix)	Draw Gear (Make)			EMSON			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"				
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)				
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT		PU PAINT	VIBGYOR	86/87		
8.2	APPLICATION OF PCN-123		SATISFACTORY				
8.3	INSUALTION		SATISFACTORY				
9.	Traceability of Furnishing Items:			Make			
i.	BRAKE EQUIPMENT			SIL			
ii.	SEAT & BERTH			SAVITRI			
iii.	WATER TANKS			AMIT			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			ORIENTAL			
vi.	WINDOWS			AGF, MECIDON			
vii.	LAV. DOORS			SAVITRI			
viii.	LP SHEET			PUNJAB LAMINATE			
ix)	BIO- TOILET			OMAX			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date
		4342	NR		GS		143539		29-09-2014
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'								
12.2	Wheel & Axle Details:	PP Side				NPP Side			
	i. Bogie No.	141061				141230			
	ii. Frame No.	ASR-298				ASR-255			
	iii. Axle No.	T-5208		5798		U-6888		V-9963	
	iv. Wheel Diameter	912.00	912.00	909.00	909.00	913.00	913.00	910.00	910.00
	v. Wheel Disc No.	38864/ 03076	38022/ 82942	03013/ 12425	03506/ 12618	41654/ 03624	41797/ 05136	41625/ 03624	38097/02 942
	vi. R.B. Nos.	U-2548	U-1720	V-657	V-1752	U-1647	U-1928	U-782	U-762
	vii. R.B. Make	FAG		FAG		FAG		FAG	
	viii. R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>								
	i.	BRAKE CYLINDER (Make)				AJT			
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE			
12.4	i.	Modification/ Trail (if any):				NIL			
	ii.	Deviations (if any):				LESS WHEEL DIA			

GS-4342



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4356	DISPATCH DATE:			10.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143542	
3.	Booked to	SSE/C&W/NDLS					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator	4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)					
ii)	Maximum length over Body	21337 ± 10					
iii)	Maximum length over Buffer	22297 ± 15					
iv)	Maximum width over Body	3245 ± 5					
v)	Maximum width over Flasher light	3402 +0/-5					
vi)	Minimum height above rail level to the lowest fitting	200 mm					
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm	1104/1104			1104/1104	
viii)	Buffer/CBC (Make)	REPL					
ix)	Draw Gear (Make)	EMSON					
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC	Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)				
		Brake release time to reach .4 Kg/cm ²	Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)				
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec	No brake application				
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec	Brakes "ON"				
7.4	Passenger alarm by pulling chain	BP Blasts out, Brakes "ON"					
7.5	Piston stroke for BMBC type coach only	19 +10/-0 mm (NAC)					
8.	PAINTING DEATAILS:						
		TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE			
8.1	PAINT	PU PAINT	VIBGYOR	86/87			
8.2	APPLICATION OF PCN-123	SATISFACTORY					
8.3	INSUALTION	SATISFACTORY					
9.	Traceability of Furnishing Items:					Make	
i.	BRAKE EQUIPMENT					SIL	
ii.	SEAT & BERTH					OVPL	
iii.	WATER TANKS					AMIT, RAIL FAB	
iv.	PVC					RESPONSIVE	
v.	FLOOR BOARD					ORIENTAL	
vi.	WINDOWS					AGF, MECIDON	
vii.	LAV. DOORS					SAVITRI	
viii.	LP SHEET					PUNJAB LAMINATE	
ix)	BIO- TOILET					OMAX	
10.	10.1	Modification/ Trial (if any):				NIL	
	10.2	Deviations (if any):				NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type	Coach No.	Dispatch Date				
		4356	NR		GS	143542	26-09-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
12.2	Wheel & Axle Details:	PP Side					NPP Side				
	i.	Bogie No.	141222					141113			
	ii.	Frame No.	RBO-1091					RBO-1065			
	iii.	Axle No.	4734		S-1851		S-1673		S-1468		
	iv.	Wheel Diameter	918.00	918.00	918.00	918.00	916.00	916.00	917.50	917.50	
	v.	Wheel Disc No.	08748/ 297	08759/ 209	06319/ 212	08067/ 246	08793/ 226	08800/ 240	08768/ 208	08833/29 9	
	vi.	R.B. Nos.	T-2283	T-2221	T-766	T-768	T-2065	T-1862	T-2270	T-2102	
	vii.	R.B. Make	FAG		FAG		FAG		FAG		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	<u>Items Traceability:</u>										
	i.	BRAKE CYLINDER (Make)					AJT				
	ii.	SECONDARY Shock Absorber (Make)					KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):					NIL				
	ii.	Deviations (if any):					NIL				

GS-4356



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. :

QMF4254;
Version: 05

1.	SHELL No:	4360	DISPATCH DATE:			11.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143540	
3.	Booked to	SSE/C&W/NDLS					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator	4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)				
	ii)	Maximum length over Body	21337 ± 10				
	iii)	Maximum length over Buffer	22297 ± 15				
	iv)	Maximum width over Body	3245 ± 5				
	v)	Maximum width over Flasher light	3402 +0/-5				
	vi)	Minimum height above rail level to the lowest fitting	200 mm				
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm	1104/1104	1104/1104		
	viii)	Buffer/CBC (Make)	REPL				
	ix)	Draw Gear (Make)	EMSON				
7.	Air Brake Testing:						
	Description			Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC	Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
			Brake release time to reach .4 Kg/cm2	Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec	No brake application			
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec	Brakes "ON"			
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	VIBGYOR	85/86		
	8.2	APPLICATION OF PCN-123		SATISFACTORY			
	8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:						
	i.	BRAKE EQUIPMENT	Make SIL				
	ii.	SEAT & BERTH	SAVITRI				
	iii.	WATER TANKS	AMIT				
	iv.	PVC	RESPONSIVE				
	v.	FLOOR BOARD	ORIENTAL				
	vi.	WINDOWS	AGF, MECIDON				
	vii.	LAV. DOORS	SAVITRI				
	viii.	LP SHEET	PUNJAB LAMINATE				
	ix)	BIO- TOILET	VICTORA				
10.	10.1	Modification/ Trial (if any):	NIL				
	10.2	Deviations (if any):	NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type	Coach No.		Dispatch Date		
		4360	NR		GS	143540		26-09-2014		
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141235				141236			
	ii.	Frame No.	ASR-376				ASR-451			
	iii.	Axle No.	3856		5034		2544		4674	
	iv.	Wheel Diameter	915.00	915.00	916.50	916.50	916.50	916.50	915.00	915.00
	v.	Wheel Disc No.	08646/ 247	08797/ 386	08845/ 226	08795/ 272	08786/ 378	08743/ 294	07347/ 277	08838/29 9
	vi.	R.B. Nos.	F-0840	F-0842	F-0839	F-0850	T-638	T-1928	F-0831	F-0821
	vii.	R.B. Make	NBC		NBC		FAG		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala Page No 1 of 3
ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4358	DISPATCH DATE:			14.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143541	
3.	Booked to	SSE/C&W/NDLS					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1103		1104/1104	
viii)	Buffer/CBC (Make)			REPL			
ix)	Draw Gear (Make)			EMSON			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT		VIBGYOR	86/87		
8.2	APPLICATION OF PCN-123			SATISFACTORY			
8.3	INSUALTION			SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
i.	BRAKE EQUIPMENT			SIL			
ii.	SEAT & BERTH			OVPL			
iii.	WATER TANKS			AMIT			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			ORIENTAL			
vi.	WINDOWS			AGF, MECIDON			
vii.	LAV. DOORS			SAVITRI			
viii.	LP SHEET			PUNJAB LAMINATE			
ix)	BIO- TOILET			OMAX			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date					
		4358	NR	GS	143541	30-09-2014					
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
12.2	Wheel & Axle Details:	PP Side				NPP Side					
	i.	Bogie No.	141245				141248				
	ii.	Frame No.	UBLS-1158				ASR-450				
	iii.	Axle No.	4983		4267		5083		5055		
	iv.	Wheel Diameter	916.00	916.00	918.00	918.00	916.00	916.00	915.50	916.00	
	v.	Wheel Disc No.	45375/ 04936	48107/ 05839	48121/ 05839	45292/ 04936	45418/ 05004	45359/ 04936	44882/ 04210	48125/05 839	
	vi.	R.B. Nos.	T1474	T1684	T2069	T1319	T2141	T2126	T2051	T2152	
	vii.	R.B. Make	FAG		FAG		FAG		FAG		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	Items Traceability:										
	i.	BRAKE CYLINDER (Make)					PEW				
	ii.	SECONDARY Shock Absorber (Make)					KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL					
	ii.	Deviations (if any):				NIL					

GS-4358



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4363	DISPATCH DATE:			14.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143545	
3.	Booked to	SSE/C&W/NDLS					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1103	1104/1104		
viii)	Buffer/CBC (Make)			REPL			
ix)	Draw Gear (Make)			EMSON			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"				
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)				
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT		PU PAINT	VIBGYOR	85/86		
8.2	APPLICATION OF PCN-123		SATISFACTORY				
8.3	INSUALTION		SATISFACTORY				
9.	Traceability of Furnishing Items:			Make			
i.	BRAKE EQUIPMENT			SIL			
ii.	SEAT & BERTH			OVPL			
iii.	WATER TANKS			AMIT			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			ORIENTAL			
vi.	WINDOWS			AGF, MECIDON			
vii.	LAV. DOORS			AMIR CHAND			
viii.	LP SHEET			PUNJAB LAMINATE			
ix)	BIO- TOILET			OMAX			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4363	NR	GS	143545	04-10-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141261				141262			
	ii.	Frame No.	RBO-1148				UBLS-1129			
	iii.	Axle No.	5120		3289		3036		3153	
	iv.	Wheel Diameter	918.00	918.00	917.50	917.50	918.00	918.00	918.00	918.00
	v.	Wheel Disc No.	48645/06275	48832/06366	47843/05721	45796/06043	45804/06043	45906/06275	48657/06275	48720/06275
	vi.	R.B. Nos.	T1280	T1286	T2166	S472	T1298	T1293	T2185	T1960
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

GS-4363



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4357	DISPATCH DATE:			14.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143543	
3.	Booked to	SSE/C&W/NDLS					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1103/1104	1104/1104		
viii)	Buffer/CBC (Make)			REPL			
ix)	Draw Gear (Make)			EMSON			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT		VIBGYOR	86/87		
8.2	APPLICATION OF PCN-123			SATISFACTORY			
8.3	INSUALTION			SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
i.	BRAKE EQUIPMENT			SIL			
ii.	SEAT & BERTH			OVPL			
iii.	WATER TANKS			AMIT			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			ORIENTAL			
vi.	WINDOWS			AGF, MECIDON			
vii.	LAV. DOORS			SAVITRI			
viii.	LP SHEET			PUNJAB LAMINATE			
ix)	BIO- TOILET			OMAX			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4357	NR	GS	143543	30-09-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141244				141238			
	ii.	Frame No.	ASR-421				ASR-443			
	iii.	Axle No.	3768		8252		4248		3859	
	iv.	Wheel Diameter	916.00	916.00	916.00	916.00	916.00	916.00	916.00	916.00
	v.	Wheel Disc No.	08844/ 219	08797/ 253	08843/ 308	08796/ 221	08789/ 256	08809/ 285	08796/ 202	77039/37 7
	vi.	R.B. Nos.	T2159	T2154	T1414	T1515	T2249	T2148	T2173	T2137
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

GS-4357



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4361	DISPATCH DATE:			15.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143544	
3.	Booked to	SSE/C&W/NDLS					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104		
viii)	Buffer/CBC (Make)			REPL			
ix)	Draw Gear (Make)			EMSON			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"				
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)				
8.	PAINTING DEATAILS:						
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT		VIBGYOR	86/87		
8.2	APPLICATION OF PCN-123		SATISFACTORY				
8.3	INSUALTION		SATISFACTORY				
9.	Traceability of Furnishing Items:			Make			
i.	BRAKE EQUIPMENT			SIL			
ii.	SEAT & BERTH			OVPL			
iii.	WATER TANKS			AMIT			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			ORIENTAL			
vi.	WINDOWS			AGF, MECIDON			
vii.	LAV. DOORS			SAVITRI			
viii.	LP SHEET			PUNJAB LAMINATE			
ix)	BIO- TOILET			OMAX			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4361	NR		GS		143544		04-10-2014	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141260				141258			
	ii.	Frame No.	ASR-456				ASR-438			
	iii.	Axle No.	4245		3044		3081		5035	
	iv.	Wheel Diameter	918.00	918.00	915.00	915.00	918.00	918.00	918.00	918.00
	v.	Wheel Disc No.	48071/ 05839	48056/ 05839	45288/ 04936	45798/ 06043	48684/ 06275	45820/ 06043	480729 /06275	48690/06 275
	vi.	R.B. Nos.	T2165	T1250	T2174	T2216	T2192	T1295	T1290	T1312
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				PEW,AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

GS-4361



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4341	DISPATCH DATE:			16.10.2014
2.	RAILWAY	NR	Type:	GS	Coach No.:	143547
3.	Booked to	SSE/C&W/DLI				
4.	Tare Weight of Coach :	36.99T				
5.	Carrying Capacity :	Seating: 90	Sleeping: NIL	Luggage: NIL		
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			200 mm		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1103/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
		TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT	VIBGYOR	86/87		
8.2	APPLICATION OF PCN-123		SATISFACTORY			
8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			SIL		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			AMIT		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			ORIENTAL		
vi.	WINDOWS			AGF, MECIDON		
vii.	LAV. DOORS			SAVITRI		
viii.	LP SHEET			PUNJAB LAMINATE		
ix)	BIO- TOILET			DARSHAN		
10.	10.1	Modification/ Trial (if any):		NIL		
	10.2	Deviations (if any):		NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type	Coach No.		Dispatch Date		
		4361	NR		GS	143547		01-10-2014		
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141255				141253			
	ii.	Frame No.	RBO-1146				ASR-469			
	iii.	Axle No.	3512		3077		3501		3577	
	iv.	Wheel Diameter	918.00	918.00	918.00	918.00	918.00	918.00	918.00	918.00
	v.	Wheel Disc No.	48005/ 05839	42578/ 03058	48735/ 06275	48082/ 05839	46043/ 03501	45799/ 06043	48842/ 06266	44911/04 210
	vi.	R.B. Nos.	S592	S849	S609	S861	S447	S357	S860	S864
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
viii	R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				AJT,PEW				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4378	DISPATCH DATE:			17.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143551	
3.	Booked to	SSE/C&W/DLI					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104		
viii)	Buffer/CBC (Make)			REPL			
ix)	Draw Gear (Make)			EMSON			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"				
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)				
8.	PAINTING DEATAILS:						
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT		VIBGYOR	86/87		
8.2	APPLICATION OF PCN-123		SATISFACTORY				
8.3	INSUALTION		SATISFACTORY				
9.	Traceability of Furnishing Items:			Make			
i.	BRAKE EQUIPMENT			SIL			
ii.	SEAT & BERTH			OVPL			
iii.	WATER TANKS			RAIL FAB			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			ORIENTAL			
vi.	WINDOWS			ABC, AGF, MECIDON			
vii.	LAV. DOORS			AMIR CHAND			
viii.	LP SHEET			PUNJAB LAMINATE			
ix)	BIO- TOILET			OMAX			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type	Coach No.	Dispatch Date			
		4378	NR		GS	143551	13-10-2014			
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141302				141296			
	ii.	Frame No.	ASR-504				ASR-372			
	iii.	Axle No.	2282		3040		3080		6456	
	iv.	Wheel Diameter	916.00	916.00	918.00	918.00	917.50	917.50	915.00	915.00
	v.	Wheel Disc No.	48630/ 06275	48001/ 05815	48679/ 06275	48644/ 06275	48686/ 06275	48155/ 05918	47997/ 05815	42164/05 208
	vi.	R.B. Nos.	F-0820	F-0577	F-0767	F-0766	F-0725	F-0722	F-0718	F-0717
	vii.	R.B. Make	NBC		NBC		NBC		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				AJT,PEW				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4376	DISPATCH DATE:			17.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143548	
3.	Booked to	SSE/C&W/DLI					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating: 90	Sleeping: NIL	Luggage: NIL			
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator	4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)					
ii)	Maximum length over Body	21337 ± 10					
iii)	Maximum length over Buffer	22297 ± 15					
iv)	Maximum width over Body	3245 ± 5					
v)	Maximum width over Flasher light	3402 +0/-5					
vi)	Minimum height above rail level to the lowest fitting	200 mm					
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm	1104/1104		1104/1104		
viii)	Buffer/CBC (Make)					REPL	
ix)	Draw Gear (Make)					EMSON	
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC	Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)				
		Brake release time to reach .4 Kg/cm2	Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)				
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec	No brake application				
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec	Brakes "ON"				
7.4	Passenger alarm by pulling chain	BP Blasts out, Brakes "ON"					
7.5	Piston stroke for BMBC type coach only	19 +10/-0 mm (NAC)					
8.	PAINTING DEATAILS:						
		TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE			
8.1	PAINT	PU PAINT	VIBGYOR	86/87			
8.2	APPLICATION OF PCN-123	SATISFACTORY					
8.3	INSUALTION	SATISFACTORY					
9.	Traceability of Furnishing Items:						
i.	BRAKE EQUIPMENT					Make SIL	
ii.	SEAT & BERTH					OVPL	
iii.	WATER TANKS					RAIL FAB	
iv.	PVC					RESPONSIVE	
v.	FLOOR BOARD					ORIENTAL	
vi.	WINDOWS					ABC, AGF, MECIDON	
vii.	LAV. DOORS					AMIR CHAND	
viii.	LP SHEET					PUNJAB LAMINATE	
ix)	BIO- TOILET					OMAX	
10.	10.1	Modification/ Trial (if any):					NIL
	10.2	Deviations (if any):					NIL



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4376	NR	GS	143548	11-10-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141292				141288			
	ii.	Frame No.	RBO-1066				ASR-491			
	iii.	Axle No.	2547		S-7480		2307		5024	
	iv.	Wheel Diameter	916.00	916.00	917.00	917.00	918.00	918.00	918.00	918.00
	v.	Wheel Disc No.	48723/ 06275	47833/ 05720	48101/ 05839	47992/ 05815	48724/ 06275	48175/ 05918	45146/ 04679	45250/04 679
	vi.	R.B. Nos.	F-0584	F-0580	F-0583	F-0587	F-0808	F-0780	F-0779	F-0758
	vii.	R.B. Make	NBC		NBC		NBC		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. :

QMF4254;
Version: 05

1.	SHELL No:	4369	DISPATCH DATE:			18.10.2014
2.	RAILWAY	NR	Type:	GS	Coach No.:	143549
3.	Booked to	SSE/C&W/DLI				
4.	Tare Weight of Coach :	36.99T				
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			200 mm		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1102	1102/1104	
viii)	Buffer/CBC (Make)			REPL		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			SIL		
ii.	SEAT & BERTH			OVPL		
iii.	WATER TANKS			RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			ORIENTAL		
vi.	WINDOWS			ABC, AGF, MECIDON		
vii.	LAV. DOORS			AMIR CHAND		
viii.	LP SHEET			NK		
ix)	BIO- TOILET			OMAX		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4369	NR	GS	143549	10-10-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141290				141283			
	ii.	Frame No.	UBLS-1140				ASR-482			
	iii.	Axle No.	P-2020		3513		Y-8556		P-3371	
	iv.	Wheel Diameter	915.00	915.00	917.00	917.00	916.50	916.00	916.00	916.00
	v.	Wheel Disc No.	41807/ 05136	41811/ 05136	48627/ 06275	48730/ 06275	41777/ 03624	37545/ 02599	41278/ 03349	41598/03 624
	vi.	R.B. Nos.	U-1929	U-1908	F-0586	F-0588	U-1445	U-1446	U-1926	U-1746
	vii.	R.B. Make	FAG		NBC		FAG		FAG	
	viii	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

GS-4369



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4359	DISPATCH DATE:			20.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143550	
3.	Booked to	SSE/C&W/DLI					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104		
viii)	Buffer/CBC (Make)			REPL			
ix)	Draw Gear (Make)			EMSON			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"				
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)				
8.	PAINTING DEATAILS:						
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT		VIBGYOR	86/87		
8.2	APPLICATION OF PCN-123		SATISFACTORY				
8.3	INSUALTION		SATISFACTORY				
9.	Traceability of Furnishing Items:			Make			
i.	BRAKE EQUIPMENT			SIL			
ii.	SEAT & BERTH			OVPL			
iii.	WATER TANKS			RAIL FAB, AMIT			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			ORIENTAL			
vi.	WINDOWS			ABC, MECIDON			
vii.	LAV. DOORS			AMIR CHAND			
viii.	LP SHEET			PUNJAB LAMINATE			
ix)	BIO- TOILET			OMAX			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date
		4359	NR	GS	143550	26-09-2014

12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141191				141121			
	ii.	Frame No.	ASR-416				RBO-1030			
	iii.	Axle No.	T-2783		5026		T-3793		S-7526	
	iv.	Wheel Diameter	917.00	917.00	916.00	916.00	918.00	918.00	918.00	918.00
	v.	Wheel Disc No.	08064/202	06980/387	08809/387	08796/263	08767/228	08801/279	08771/215	08835/204
	vi.	R.B. Nos.	T-2194	T-2195	T-2206	T-2173	T-2229	U-759	T-2260	T-1677
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4374	DISPATCH DATE:			22.10.2014	
2.	RAILWAY	NR	Type:	GS	Coach No.:	143552	
3.	Booked to	SSE/C&W/DLI					
4.	Tare Weight of Coach :	36.99T					
5.	Carrying Capacity :	Seating:	90	Sleeping:	NIL	Luggage:	NIL
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			200 mm			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1102	1102/1104		
viii)	Buffer/CBC (Make)			REPL			
ix)	Draw Gear (Make)			EMSON			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"				
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)				
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT		PU PAINT	VIBGYOR	85/86		
8.2	APPLICATION OF PCN-123		SATISFACTORY				
8.3	INSUALTION		SATISFACTORY				
9.	Traceability of Furnishing Items:			Make			
i.	BRAKE EQUIPMENT			SIL			
ii.	SEAT & BERTH			OVPL			
iii.	WATER TANKS			AMIT			
iv.	PVC			RESPONSIVE			
v.	FLOOR BOARD			ORIENTAL			
vi.	WINDOWS			ABC, MECIDON			
vii.	LAV. DOORS			AMIR CHAND			
viii.	LP SHEET			PUNJAB LAMINATE			
ix)	BIO- TOILET			OMAX			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4374	NR	GS	143552	13-10-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i. Bogie No.	141301				141297				
	ii. Frame No.	ASR-200				ASR-492				
	iii. Axle No.	6455		3567		T-4880		4295		
	iv. Wheel Diameter	917.50	917.50	916.00	916.00	915.00	915.00	916.50	916.00	
	v. Wheel Disc No.	47882/05815	48126/05839	48119/05839	48088/05839	41536/03604	41514/03604	45373/04936	45313/04936	
	vi. R.B. Nos.	F-0709	F-0743	F-0621	F-0581	U-1440	U-1428	F-0805	F-0582	
	vii. R.B. Make	NBC		NBC		FAG		NBC		
	viii. R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				PEW				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

GS-4374