



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4049	DISPATCH DATE:			10.10.2014
2.	RAILWAY	ECoR	Type:	GSLRD	Coach No.:	14709
3.	Booked to			SSE/C&W/VSKP		
4.	Tare Weight of Coach :		37.10 T			
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm 9AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			REPL		
ix)	Draw Gear (Make)			CFPL		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	86/87	
8.2	APPLICATION OF PCN-123		SATISFACTORY			
8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			SIL		
ii.	SEAT & BERTH			MOHAN		
iii.	WATER TANKS			RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			OVPL		
vi.	UIC VESTIBULE			NA		
vii.	LAV. DOORS			NA		
viii.	LP SHEET			NK		
ix)	BIO- TOILET			OMAX		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date					
		4049	ECOR	GSLRD	14709	27-09-2014					
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
12.2	Wheel & Axle Details:	PP Side					NPP Side				
	i.	Bogie No.	141231					141128			
	ii.	Frame No.	ASR-386					UBLS-1048			
	iii.	Axle No.	RWF-39572		5023		3863		3375		
	iv.	Wheel Diameter	918.00	918.00	916.00	916.00	918.00	918.00	918.00	918.00	
	v.	Wheel Disc No.	08800/262	08801/294	06376/213	08763/239	08791/262	08829/268	08797/259	08786/204	
	vi.	R.B. Nos.	E-2469	E-2486	T-2010	T-614	E-2788	E-2443	E-2452	E-2473	
	vii.	R.B. Make	NBC		FAG		NBC		NBC		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	Items Traceability:										
	i.	BRAKE CYLINDER (Make)					AJT				
	ii.	SECONDARY Shock Absorber (Make)					KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):					NIL				
	ii.	Deviations (if any):					NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4051	DISPATCH DATE:			14.10.2014
2.	RAILWAY	ECoR	Type:	GSLRD	Coach No.:	14708
3.	Booked to		SSE/C&W/VSKP			
4.	Tare Weight of Coach :		37.10 T			
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm 9AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			REPL		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			SIL		
ii.	SEAT & BERTH			MOHAN		
iii.	WATER TANKS			AMIT & RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			OVPL		
vi.	UIC VESTIBULE			NA		
vii.	LAV. DOORS			SAVITRI		
viii.	LP SHEET			NA		
ix)	BIO- TOILET			OMAX		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4051	ECOR	GSLRD	14708	26-09-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141131				141220			
	ii.	Frame No.	UBLS-1014				UBLS-1098			
	iii.	Axle No.	V-0963		3855		3854		3832	
	iv.	Wheel Diameter	918.00	918.00	916.50	916.50	918.00	918.00	916.00	916.00
	v.	Wheel Disc No.	08794/294	08837/308	08727/224	08847/385	08796/270	08797/378	08791/380	08797/205
	vi.	R.B. Nos.	T-1931	T-1903	T-2171	T-2176	T-533	T-668	T-964	T-1185
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

DSL-4051



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4054	DISPATCH DATE:			14.10.2014
2.	RAILWAY	ECoR	Type:	GSLRD	Coach No.:	14710
3.	Booked to		SSE/C&W/VSKP			
4.	Tare Weight of Coach :		37.10 T			
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T
6.	Shell Details: (SG-90004 alt 'b')					
	6.1	Leading Dimensions;				
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)	
	ii)	Maximum length over Body			21337 ± 10	
	iii)	Maximum length over Buffer			22297 ± 15	
	iv)	Maximum width over Body			3245 ± 5	
	v)	Maximum width over Flasher light			3402 +0/-5	
	vi)	Minimum height above rail level to the lowest fitting			181.5 mm 9AE63143)	
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104
	viii)	Buffer/CBC (Make)			REPL	
	ix)	Draw Gear (Make)			EMSON	
7.	Air Brake Testing:					
		Description			Specified	
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)	
			Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)	
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application	
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"	
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"		
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE	
	8.1	PAINT	PU PAINT	VIBGYOR	86/87	
	8.2	APPLICATION OF PCN-123		SATISFACTORY		
	8.3	INSUALTION		SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
	i.	BRAKE EQUIPMENT		SIL		
	ii.	SEAT & BERTH		MOHAN		
	iii.	WATER TANKS		AMIT		
	iv.	PVC		RESPONSIVE		
	v.	FLOOR BOARD		OVPL		
	vi.	UIC VESTIBULE		NA		
	vii.	LAV. DOORS		ANKUR, RCF		
	viii.	LP SHEET		PUNJAB LAMINATES		
	ix)	BIO- TOILET		OMAX		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4054	ECOR	GSLRD	14710	16-08-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141035				140967			
	ii.	Frame No.	ASR-290				ASR-188			
	iii.	Axle No.	V-9090		W-2763		T-5250		S-7554	
	iv.	Wheel Diameter	917.50	917.50	917.50	917.50	918.00	918.00	918.00	918.00
	v.	Wheel Disc No.	06357/378	08077/270	06300/276	06357/255	06325/206	06307/284	06303/248	06341/213
	vi.	R.B. Nos.	U-1419	U-1436	U-1743	U-1762	U-363	U-377	U-2490	U-372
	vii.	R.B. Make	NBC		NBC		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

DSL-4054