



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4025	DISPATCH DATE:			6.8.2014
2.	RAILWAY	NC	Type:	GSLRD	Coach No.:	14793
3.	Booked to	SSE/C&W/AGC				
4.	Tare Weight of Coach :	37.10 T				
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm 9AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	86/87	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			AMIT & RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			OVPL		
vi.	UIC VESTIBULE			NA		
vii.	LAV. DOORS			SAVITRI & ANKUR		
viii.	LP SHEET			PUNJAB LAMINATES		
ix)	BIO- TOILET			M K PRECISION		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4025	NC		SLR		14793		26-07-2014	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	140918				140920			
	ii.	Frame No.	ASR-170				ASR-165			
	iii.	Axle No.	1548		V-0003		S-6897		V-9129	
	iv.	Wheel Diameter	916.00	916.00	915.00	915.00	917.50	917.00	917.00	916.50
	v.	Wheel Disc No.	03688/ 216	04200/ 290	02634/ 224	99270/ 227	06486/ 260	06838/ 369	06284/ 249	06913/25 3
	vi.	R.B. Nos.	E-2586	E-2585	E-2270	E-2223	E-2692	E-2690	E-2441	E-2470
	vii.	R.B. Make	NBC		NBC		NBC		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4026	DISPATCH DATE:			2.8.2014
2.	RAILWAY	NC	Type:	GSLRD	Coach No.:	14792
3.	Booked to	SSE/C&W/AGC				
4.	Tare Weight of Coach :	37.10 T				
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm 9AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		ADVANCE	85/86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			AMIT & RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			OVPL		
vi.	UIC VESTIBULE			NA		
vii.	LAV. DOORS			SAVITRI, AMIR CHAND & ANKUR		
viii.	LP SHEET			PUNJAB LAMINATES		
ix)	BIO- TOILET			OMAX		
10.	10.1	Modification/ Trial (if any):		NIL		
	10.2	Deviations (if any):		NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4026	NC		GSLRD		14792		18-07-2014	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	140895				140897			
	ii.	Frame No.	UBLS-18805				UBLS-18839			
	iii.	Axle No.	U-8579		Y-6331		V-0277		V-0913	
	iv.	Wheel Diameter	915.00	915.50	915.50	915.00	915.00	915.00	915.00	915.00
	v.	Wheel Disc No.	99119/ 344	05592/ 261	02158/ 250	88274/ 209	05666/ 372	06369/ 288	05674/ 247	05824/21 1
	vi.	R.B. Nos.	E-2566	E-2562	E-2431	E-2317	X-1997	X-2002	X-1948	X-1945
	vii.	R.B. Make	NBC		NBC		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

DSLRL-4026



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4027	DISPATCH DATE:			7.8.2014
2.	RAILWAY	NC	Type:	GSLRD	Coach No.:	14795
3.	Booked to	SSE/C&W/ALD				
4.	Tare Weight of Coach :	37.10 T				
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm 9AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT		PU PAINT	VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			AMIT & RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			TAYAL		
vi.	UIC VESTIBULE			NA		
vii.	LAV. DOORS			AMIR CHAND, SAVITRI & ANKUR		
viii.	LP SHEET			PUNJAB LAMINATES		
ix)	BIO- TOILET			M K PRECISION		
10.	10.1	Modification/ Trial (if any):		NIL		
	10.2	Deviations (if any):		NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4027	NC		GSLRD		14795		15-07-2014	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	140910				140919			
	ii.	Frame No.	ASR-146				ASR-169			
	iii.	Axle No.	Y-6267		V-9683		W-2921		S-5691	
	iv.	Wheel Diameter	916.50	916.00	916.50	916.00	917.00	917.00	917.00	917.00
	v.	Wheel Disc No.	06318/ 267	06838/ 241	06366/ 217	06330/ 269	06843/ 270	03849/ 259	03770/ 273	03763/25 9
	vi.	R.B. Nos.	E2446	E2475	E2474	E2438	E2660	E2697	E2448	E2467Y
	vii.	R.B. Make	NBC		NBC		NBC		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4029	DISPATCH DATE:			11.8.2014
2.	RAILWAY	NC	Type:	GSLRD	Coach No.:	14796
3.	Booked to	SSE/C&W/CNB				
4.	Tare Weight of Coach :	37.10 T				
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm 9AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			AMIT		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			ORIENTAL		
vi.	UIC VESTIBULE			NA		
vii.	LAV. DOORS			AMIR CHAND,SAVITRI & ANKUR		
viii.	LP SHEET			PUNJAB LAMINATES		
ix)	BIO- TOILET			OMAX		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4029	NC		GSLRD		14796		31-07-2014	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	140937				140944			
	ii.	Frame No.	ASR-1192				ASR-173			
	iii.	Axle No.	W-2372		S-5628		W-3166		V-9292	
	iv.	Wheel Diameter	917.00	917.00	917.50	917.00	916.00	916.00	915.00	915.00
	v.	Wheel Disc No.	06857/ 381	06965/ 201	04096/ 286	06338/ 384	94192/ 365	00612/ 217	06298/ 375	06293/26 0
	vi.	R.B. Nos.	E2186	E2182	E2212	E2165	E2297	E2188	X1990	X1980
	vii.	R.B. Make	NBC		NBC		NBC		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4032	DISPATCH DATE:			9.8.2014
2.	RAILWAY	NC	Type:	GSLRD	Coach No.:	14794
3.	Booked to	SSE/C&W/JHS				
4.	Tare Weight of Coach :	37.10 T				
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm 9AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT		PU PAINT	VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123		SATISFACTORY			
8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			ORIENTAL		
vi.	UIC VESTIBULE			NA		
vii.	LAV. DOORS			AMIR CHAND, SAVITRI & ANKUR		
viii.	LP SHEET			PUNJAB LAMINATES		
ix)	BIO- TOILET			OMAX		
10.	10.1	Modification/ Trial (if any):		NIL		
	10.2	Deviations (if any):		NIL		



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4032	NC	GSLRD	14794	14-07-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	140844				140845			
	ii.	Frame No.	ASR-73				ASR-1299			
	iii.	Axle No.	7633		8762		8582		1748	
	iv.	Wheel Diameter	917.00	917.00	915.00	915.00	916.00	916.00	915.00	915.00
	v.	Wheel Disc No.	06258/258	06236/257	06704/253	06395/315	06296/213	06317/210	06150/243	06150/213
	vi.	R.B. Nos.	E-2812	E-2833	E-2850	E-2860	E-2257	E-2256	E-2841	E-2840
	vii.	R.B. Make	NBC		NBC		NBC		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				AJT				
ii.	SECONDARY Shock Absorber (Make)				GABRIEL					
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

DSL-4032