



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4045	DISPATCH DATE:				15.9.2014
2.	RAILWAY	NCR	Type:	GSLRD	Coach No.:	14797	
3.	Booked to			SSE/C&W/CNB			
4.	Tare Weight of Coach :			37.10 T			
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T	
6.	Shell Details: (SG-90004 alt 'b')						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
	ii)	Maximum length over Body			21337 ± 10		
	iii)	Maximum length over Buffer			22297 ± 15		
	iv)	Maximum width over Body			3245 ± 5		
	v)	Maximum width over Flasher light			3402 +0/-5		
	vi)	Minimum height above rail level to the lowest fitting			200 mm		
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm	1104/1104	1104/1104		
	viii)	Buffer/CBC (Make)			REPL		
	ix)	Draw Gear (Make)			CFPL		
7.	Air Brake Testing:						
		Description		Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC	Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
			Brake release time to reach .4 Kg/cm2	Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec	No brake application			
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec	Brakes "ON"			
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	VIBGYOR	86/87`		
	8.2	APPLICATION OF PCN-123		SATISFACTORY			
	8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
	i.	BRAKE EQUIPMENT		SIL			
	ii.	SEAT & BERTH		SAVITRI			
	iii.	WATER TANKS		AMIT			
	iv.	PVC		RESPONSIVE			
	v.	FLOOR BOARD		ORIENTAL			
	vi.	UIC VESTIBULE		NA			
	vii.	LAV. DOORS		SAVITRI, AMIR CHAND & ANKUR			
	viii.	LP SHEET		NK			
	ix)	BIO- TOILET		OMAX			
10.	10.1	Modification/ Trial (if any):		NIL			
	10.2	Deviations (if any):		NIL			



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4045	NCR		GSLRD		14797		12-09-2014	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141167				141168			
	ii.	Frame No.	RBO-1096				ASR-403			
	iii.	Axle No.	U-8270		S-1522		U-4968		S-5398	
	iv.	Wheel Diameter	918.00	918.00	918.00	918.00	918.00	918.00	917.00	917.00
	v.	Wheel Disc No.	06881/260	06981/269	08082/252	06397/369	08080/213	03794/255	06948/232	08077//268
	vi.	R.B. Nos.	U-1412	U-1404	U-771	U-2498	U-1393	U-1866	U-2540	U-2491
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4035	DISPATCH DATE:			26.9.2014
2.	RAILWAY	NCR	Type:	GSLRD	Coach No.:	14798
3.	Booked to			SSE/C&W/GKP		
4.	Tare Weight of Coach :			37.10 T		
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			200 mm		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT		PU PAINT	VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			SIL		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			AMIT, RAIL FAB		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			ORIENTAL		
vi.	UIC VESTIBULE			NA		
vii.	LAV. DOORS			SAVITRI, RCF & ANKUR		
viii.	LP SHEET			NK		
ix)	BIO- TOILET			OMAX		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4035	NCR		GSLRD		14798		11-09-2014	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141166				141172			
	ii.	Frame No.	ASR-303				UBLS-1115			
	iii.	Axle No.	W-2878		5229		S-1825		S-9214	
	iv.	Wheel Diameter	918.00	918.00	918.00	918.00	917.00	917.00	918.00	918.00
	v.	Wheel Disc No.	07033/284	07131/206	05842/260	07133/208	07030/241	07028/378	08070/377	06963/278
	vi.	R.B. Nos.	T-2146	T-2131	U-1411	U-1516	U-338	U-371	U-766	U-2498
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR-BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				