



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

| | | | | | | |
|-----|-----------------------------------|---|---------------------------------------|-----------|--|--------------|
| 1. | SHELL No: | 4025 | DISPATCH DATE: | | | 30.10.2014 |
| 2. | Rly: | NR | Type: | MEMU/TC2 | Coach No.: | 31292 |
| 3. | Booked to | SSE/C&W/GZB | | | | |
| 4. | Tare Weight of Coach : | 33.15 T | | | | |
| 5. | Carrying Capacity : | Seating: | 80 | Standing | 272 | Luggage: NIL |
| 6. | Shell Details: (SG-90004 alt 'b') | | | | | |
| | 6.1 Leading Dimensions; | | | | | |
| | i) | Maximum height above rail to top of Roof ventilator | | | 4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only) | |
| | ii) | Maximum length over Body | | | 21337 ± 10 | |
| | iii) | Maximum length over Buffer | | | 22297 ± 15 | |
| | iv) | Maximum width over Body | | | 3245 ± 5 | |
| | v) | Maximum width over Flasher light | | | 3402 +0/-5 | |
| | vi) | Minimum height above rail level to the lowest fitting | | | 181.5 mm (AE63143) | |
| | vii) | Buffer/CBC Height | Specified : 1104 +0 /-10 mm | | NA | NA |
| | vii) | Make : | NA | | | |
| | ix) | Shaku Coupler Height | Specified : 1035 +0 /-5 mm | | 1035/1035 | |
| | x) | Shaku Coupler Make: | SANROK | | | |
| 7. | Air Brake Testing: | | | | | |
| | Description | | | Specified | | |
| | 7.1 | Emergency Application | Time for 0 to 3.6 Kg/cm2 of BC | | Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type) | |
| | | | Brake release time to reach .4 Kg/cm2 | | Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type) | |
| | 7.2 | Insensitivity | BP dipped @ 0.30 Kg/cm2 n 60 sec | | No brake application | |
| | 7.3 | Sensitivity | BP dipped @ 0.60 Kg/cm2 in 6 sec | | Brakes "ON" | |
| | 7.4 | Passenger alarm by pulling chain | | | BP Blasts out, Brakes "ON" | |
| | 7.5 | Piston stroke for BMBC type coach only | | | 19 +10/-0 mm (NAC) | |
| 8. | PAINTING DEATAILS: | | | | | |
| | | | TYPE OF PAINT | MAKE | AVERAGE GLOSS VALUE | |
| | 8.1 | PAINT | PU PAINT | ADVANCE | 85/86 | |
| | 8.2 | APPLICATION OF PCN-123 | SATISFACTORY | | | |
| | 8.3 | INSUALTION | SATISFACTORY | | | |
| 9. | Traceability of Furnishing Items: | | | Make | | |
| | i. | BRAKE EQUIPMENT | | | ESCORTS | |
| | ii. | SEAT & BERTH | | | MOHAN | |
| | lii | PVC | | | RESPONSIVE | |
| | Iv | FLOOR BOARD | | | ORIENTAL | |
| | V | UIC VESTIBULE | | | KRP | |
| | Vi | LP SHEETS | | | PUNJAB LAMINATE | |
| | Vii | BODY SIDE WINDOW | | | ABC | |
| | Viii | EMERGENCY WINDOW | | | ABC | |
| | Xi | DOOR WINDOW | | | AGF | |
| | X | WATER TANK | | | RUBICON | |
| | Xi | LAV WINDOW | | | MECIDON | |
| | xii | LAV DOOR | | | SAVITRI | |
| 10. | 10.1 | Modification/ Trial (if any): | | | NIL | |
| | 10.2 | Deviations (if any): | | | NIL | |



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

| | | | | | | | | | | |
|------|--|---------------------------------|---|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| 12. | Bogie Details: | Shell No. | Railway | Type | Coach No. | Dispatch Date | | | | |
| | | 4025 | nr | MEMU-TC | 31292 | 27-10-2014 | | | | |
| 12.1 | BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a' | | | | | | | | | |
| 12.2 | Wheel & Axle Details: | PP Side | | | | NPP Side | | | | |
| | i. | Bogie No. | 145116 | | | | 145115 | | | |
| | ii. | Frame No. | ASR-104 | | | | ASR-112 | | | |
| | iii. | Axle No. | W-2431 | | Y-6880 | | RWF-110373 | | U-4164 | |
| | iv. | Wheel Diameter | 952.00 | 952.00 | 952.00 | 952.00 | 952.00 | 952.00 | 955.00 | 955.00 |
| | v. | Wheel Disc No. | 06296/ 945 | 93809/ 937 | 06310/ 944 | 06282/ 946 | 06266/ 944 | 06361/ 958 | 02306/ 949 | 05571/92 9 |
| | vi. | R.B. Nos. | U-2465 | U-2453 | F-0841 | F-0813 | F-0844 | F-0814 | U-1620 | U-1606 |
| | vii. | R.B. Make | FAG | | NBC | | NBC | | FAG | |
| | viii. | R.B. Type | Direct Mounted Spherical Roller Bearing | | | | | | | |
| 12.3 | Items Traceability: | | | | | | | | | |
| | i. | BRAKE CYLINDER (Make) | | | | PEW | | | | |
| | ii. | SECONDARY Shock Absorber (Make) | | | | KNOR-BREMSE | | | | |
| 12.4 | i. | Modification/ Trail (if any): | | | | NIL | | | | |
| | ii. | Deviations (if any): | | | | NIL | | | | |

MEMU/TC2—4025