



ROLLING STOCK CERTIFICATE

Form No. :

QMF4254;  
Version: 05

1.	SHELL No:	<b>4200</b>	DISPATCH DATE:			<b>10.03.2015</b>	
2.	RAILWAY	<b>WCR</b>	Type:	<b>WGACCN</b>	Coach No.:	<b>15113</b>	
3.	Booked to	<b>SSE/C&amp;W/JBP</b>					
4.	Tare Weight of Coach :	<b>52.53 T</b>					
5.	Carrying Capacity :	Seating:	<b>64</b>	Sleeping:	<b>64</b>	Luggage:	<b>NIL</b>
6.	Shell Details: (SG-90004 alt 'b')						
6.1	Leading Dimensions;						
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body			21337 ± 10			
iii)	Maximum length over Buffer			22297 ± 15			
iv)	Maximum width over Body			3245 ± 5			
v)	Maximum width over Flasher light			3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting			181.5 mm (AE63143)			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm	<b>1104/1103</b>	<b>1104/1104</b>			
viii)	Buffer/CBC (Make )			<b>JLS</b>			
ix)	Draw Gear (Make)			<b>EMSON</b>			
7.	Air Brake Testing:						
	Description			Specified			
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application			
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"			
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"				
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)				
8.	PAINTING DEATAILS:						
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT		<b>VIBGYOR</b>	<b>85/86</b>		
8.2	APPLICATION OF PCN-123		<b>SATISFACTORY</b>				
8.3	INSUALTION		<b>SATISFACTORY</b>				
9.	Traceability of Furnishing Items:			Make			
i.	BRAKE EQUIPMENT			<b>ESCORTS</b>			
ii.	SEAT & BERTH			<b>OVPL</b>			
iii.	WATER TANKS			<b>SHIVALIK, RAIL FAB</b>			
iv.	PVC			<b>RESPONSIVE</b>			
v.	FLOOR BOARD			<b>TAYAL</b>			
vi.	UIC VESTIBULE			<b>KRP</b>			
vii.	LAV. DOORS			<b>DHINJAN</b>			
viii.	LP SHEET			<b>LP</b>			
ix)	BIO- TOILET			<b>RAIL FAB</b>			
10	10.1	Modification/ Trial (if any):			<b>NIL</b>		
.	10.2	Deviations (if any):			<b>NIL</b>		



12.	<b>Bogie Details:</b>	<b>Shell No.</b>	<b>Railway</b>	<b>Type</b>	<b>Coach No.</b>	<b>Dispatch Date</b>					
		4200	WCR	WGACCN	15113	20-02-2015					
12.1	<b>BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'</b>										
12.2	<b>Wheel &amp; Axle Details:</b>	<b>PP Side</b>				<b>NPP Side</b>					
	i.	<b>Bogie No.</b>	153079				153080				
	ii.	<b>Frame No.</b>	UBLS-4507				UBLS-4512				
	iii.	<b>Axle No.</b>	9677		P-6114		A-4161		7702		
	iv.	<b>Wheel Diameter</b>	916.50	917.00	917.00	916.50	916.50	917.00	917.00	917.00	
	v.	<b>Wheel Disc No.</b>	10282/ 239	10136/ 212	10301/ 214	10206/ 378	10181/ 252	10305/ 273	10367/ 290	10305/25 1	
	vi.	<b>R.B. Nos.</b>	K2370	J2162	K2500	K2453	J2227	J2245	J1916	K2411	
	vii.	<b>R.B. Make</b>	NBC		NBC		NBC		NBC		
	viii.	<b>R.B. Type</b>	Direct Mounted Spherical Roller Bearing								
12.3	<b>Items Traceability:</b>										
	i.	<b>BRAKE CYLINDER (Make)</b>					AJT,PEW				
	ii.	<b>SECONDARY Shock Absorber (Make)</b>					KNORR BREMSE				
12.4	i.	<b>Modification/ Trail (if any):</b>					NIL				
	ii.	<b>Deviations (if any):</b>					NIL				

WGACCN-4200



**ROLLING STOCK CERTIFICATE**

Form No. :

QMF4254;  
Version: 05

1.	SHELL No:	<b>4186</b>	DISPATCH DATE:			<b>21.03.2015</b>
2.	RAILWAY	<b>WCR</b>	Type:	<b>WGACCN</b>	Coach No.:	<b>15114</b>
3.	Booked to	<b>SSE/C&amp;W/JBP</b>				
4.	Tare Weight of Coach :	<b>52.53 T</b>				
5.	Carrying Capacity :	Seating:	<b>64</b>	Sleeping:	<b>64</b>	Luggage: <b>NIL</b>
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm (AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm	<b>1102/1104</b>	<b>1104/1100</b>		
viii)	Buffer/CBC (Make )			<b>JLS</b>		
ix)	Draw Gear (Make)			<b>EMSON</b>		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		<b>VIBGYOR</b>	<b>85/85</b>	
8.2	APPLICATION OF PCN-123		<b>SATISFACTORY</b>			
8.3	INSUALTION		<b>SATISFACTORY</b>			
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			<b>ESCORTS</b>		
ii.	SEAT & BERTH			<b>OVPL</b>		
iii.	WATER TANKS			<b>SHIVALIK, RUBICONE</b>		
iv.	PVC			<b>RESPONSIVE</b>		
v.	FLOOR BOARD			<b>TAYAL</b>		
vi.	UIC VESTIBULE			<b>KRP</b>		
vii.	LAV. DOORS			<b>DHINJAN</b>		
viii.	LP SHEET			<b>NA</b>		
ix)	BIO- TOILET			<b>RAIL FAB</b>		
10	10.1	Modification/ Trial (if any):			<b>NIL</b>	
.	10.2	Deviations (if any):			<b>NIL</b>	



12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4186	WCR		WGACCN		15114		26-02-2015	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side					NPP Side			
	i.	Bogie No.	153095					153097		
	ii.	Frame No.	UBLS-4522					UBLS-4484		
	iii.	Axle No.	10133		RWF-105461		RWF-97693		A-4394	
	iv.	Wheel Diameter	916.50	917.00	916.50	916.50	916.50	917.00	917.00	916.50
	v.	Wheel Disc No.	10360/264	10309/221	10257/256	10130/242	10350/276	10280/222	10361/240	10364/384
	vi.	R.B. Nos.	K-2464	K-2502	K-2128	K-2143	J-2002	J-2017	J-1834	J-1857
	vii.	R.B. Make	NBC		NBC		NBC		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)					PEW,AJT			
	ii.	SECONDARY Shock Absorber (Make)					KNORR BREMSE			
12.4	i.	Modification/ Trail (if any):					NIL			
	ii.	Deviations (if any):					NIL			

WGACCN-4186