



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4027	DISPATCH DATE:			25.7.2014
2.	RAILWAY	NCR	Type:	WGACCN	Coach No.:	14124
3.	Booked to	SSE/C&W/CNB				
4.	Tare Weight of Coach :	52.53 T				
5.	Carrying Capacity :	Seating:	64	Sleeping:	64	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm (AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			SHIVALIK & AMIT		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			NARBADA		
vi.	UIC VESTIBULE			KRP		
vii.	LAV. DOORS			RCF		
viii.	LP SHEET			NA		
ix)	BIO- TOILET			RAIL FAB		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4027	NC		WGACCN		14124		10-06-14	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	143231				143228			
	ii.	Frame No.	UBLS-4193				UBLS-4177			
	iii.	Axle No.	0893		7793		1265		1074	
	iv.	Wheel Diameter	916.50	916.50	917.00	917.00	913.00	912.50	911.00	911.00
	v.	Wheel Disc No.	24899/ 15035	24894/ 15035	24912/ 15035	24890/ 15035	55569/ 02365	52489/ 08919	14905/ 16111	15578/15 905
	vi.	R.B. Nos.	Y-990	X-1492	X-1872	X-1881	X-1669	X-1686	X-1667	Y-1591
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				PEW,AJT				
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				LESS WHEEL DIA USED				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4028	DISPATCH DATE:			30.7.2014
2.	RAILWAY	NCR	Type:	WGACCN	Coach No.:	14125
3.	Booked to	SSE/C&W/CNB				
4.	Tare Weight of Coach :	52.53 T				
5.	Carrying Capacity :	Seating:	64	Sleeping:	64	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm (AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1103	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			SHIVALIK & AMIT		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			NARBADA		
vi.	UIC VESTIBULE			KRP		
vii.	LAV. DOORS			RCF		
viii.	LP SHEET			PUNJAB LAMINATES		
ix)	BIO- TOILET			RAIL FAB		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date
		4028	NC		WGACCN		14125		27-06-2014
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'								
12.2	Wheel & Axle Details:	PP Side				NPP Side			
	i. Bogie No.	143214				143243			
	ii. Frame No.	UBLS-4192				UBLS-4229			
	iii. Axle No.	0742		2720		2134		1919	
	iv. Wheel Diameter	918.00	918.00	916.00	916.00	917.00	917.00	918.00	918.00
	v. Wheel Disc No.	06951/274	06947/384	06949/264	06272/228	06946/206	06981/248	06945/318	06974/227
	vi. R.B. Nos.	D-0935	D0934	X1724	X623	X1737	X1720	D-0941	D0908
	vii. R.B. Make	NBC		FAG		FAG		NBC	
	viii. R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>								
	i.	BRAKE CYLINDER (Make)				AJT			
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL			
12.4	i.	Modification/ Trail (if any):				NIL			
	ii.	Deviations (if any):				NIL			



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4033	DISPATCH DATE:			07.08.2014
2.	RAILWAY	NCR	Type:	WGACCN	Coach No.:	14126
3.	Booked to	SSE/C&W/CNB				
4.	Tare Weight of Coach :	52.53 T				
5.	Carrying Capacity :	Seating:	64	Sleeping:	64	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm (AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1102/1103	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		ADVANCE	86/87	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			SHIVALIK & AMIT		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			NARBADA		
vi.	UIC VESTIBULE			KRP		
vii.	LAV. DOORS			RCF		
viii.	LP SHEET			PUNJAB LAMINATES		
ix)	BIO- TOILET			MK		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date			
		4033	NC	WGACCN	14586	28-06-2014			
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'								
12.2	Wheel & Axle Details:	PP Side				NPP Side			
	i. Bogie No.	143217				143236			
	ii. Frame No.	UBLS-950				UBLS-4239			
	iii. Axle No.	1907		2139		2188		1920	
	iv. Wheel Diameter	915.50	915.50	915.00	915.00	815.00	815.00	916.50	916.00
	v. Wheel Disc No.	27964/ 15580	27961/ 15580	28048/ 15580	28015/ 15580	28127/ 16013	28555/ 17063	25445/ 15305	28068/ 15580
	vi. R.B. Nos.	D-0500	D-0484	X-1763	X-596	Y-1001	Y-1037	X-1226	X-1922
	vii. R.B. Make	NBC		FAG		FAG		NBC	
	viii. R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>								
	i.	BRAKE CYLINDER (Make)				AJT			
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL			
12.4	i.	Modification/ Trail (if any):				NIL			
	ii.	Deviations (if any):				NIL			

WGACCN-4033



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4031	DISPATCH DATE:			09.08.2014
2.	RAILWAY	NCR	Type:	WGACCN	Coach No.:	14127
3.	Booked to	SSE/C&W/CNB				
4.	Tare Weight of Coach :	52.53 T				
5.	Carrying Capacity :	Seating:	64	Sleeping:	64	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm (AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			HEPL		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm2		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	86/87	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			SHIVALIK & AMIT		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			TAYAL		
vi.	UIC VESTIBULE			KRP		
vii.	LAV. DOORS			RCF		
viii.	LP SHEET			NK		
ix)	BIO- TOILET			MK		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4031	NC		WGACCN		14127		30-05-14	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	143185				143198			
	ii.	Frame No.	UBLS-1002				UBLS-4232			
	iii.	Axle No.	6235		V-9473		U-4796		S-3552	
	iv.	Wheel Diameter	913.50	913.00	910.00	910.00	915.00	915.00	915.00	915.00
	v.	Wheel Disc No.	03015/ 12425	62657/ 10945	55046/ 09010	55773/ 02612	54999/ 09010	62872/ 10845	17146/ 16294	17201/16 294
	vi.	R.B. Nos.	X-1441	Y-2019	Y-2027	Y-1623	X-2402	X-2417	B-0842	B-0826
	vii.	R.B. Make	FAG		FAG		FAG		NBC	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				PEW				
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				LESS WHEEL DIA USED				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4032	DISPATCH DATE:			07.08.2014
2.	RAILWAY	NCR	Type:	WGACCN	Coach No.:	14128
3.	Booked to	SSE/C&W/CNB				
4.	Tare Weight of Coach :	52.53 T				
5.	Carrying Capacity :	Seating:	64	Sleeping:	64	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm (AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1102/1100	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	85/86	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			SHIVALIK & AMIT		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			NARBADA		
vi.	UIC VESTIBULE			KRP		
vii.	LAV. DOORS			SAVITRI		
viii.	LP SHEET			PUNJAB LAMINATES		
ix)	BIO- TOILET			OMAX		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date	
		4032	NCR		WGACCN		14128		30-05-14	
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	143162				143188			
	ii.	Frame No.	UBLS-928				UBLS-4196			
	iii.	Axle No.	6002		7840		695		RWF-98924	
	iv.	Wheel Diameter	910.00	91.00	914.00	914.00	913.00	913.00	917.00	917.00
	v.	Wheel Disc No.	02543/ 04066	00141/ 08625	33657/ 00474	03410/ 12547	50474/ 07798	54613/ 09576	15082/ 16142	18984/16 671
	vi.	R.B. Nos.	Y2005	Y1606	Y2057	Y2125	X2019	X1710	Y1530	Y1493
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	<u>Items Traceability:</u>									
	i.	BRAKE CYLINDER (Make)				AJT,PEW				
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				LESS WHEEL DIA USED				

WGACCN-4032



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	4040	DISPATCH DATE:			12.08.2014
2.	RAILWAY	NCR	Type:	WGACCN	Coach No.:	14129
3.	Booked to	SSE/C&W/CNB				
4.	Tare Weight of Coach :	52.53 T				
5.	Carrying Capacity :	Seating:	64	Sleeping:	64	Luggage: NIL
6.	Shell Details: (SG-90004 alt 'b')					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5 mm (AE63143)		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain			BP Blasts out, Brakes "ON"		
7.5	Piston stroke for BMBC type coach only			19 +10/-0 mm (NAC)		
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		ADVANCE	86/87	
8.2	APPLICATION OF PCN-123			SATISFACTORY		
8.3	INSUALTION			SATISFACTORY		
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORTS		
ii.	SEAT & BERTH			SAVITRI		
iii.	WATER TANKS			SHIVALIK & AMIT		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			OVPL		
vi.	UIC VESTIBULE			KRP		
vii.	LAV. DOORS			RCF		
viii.	LP SHEET			PUNJAB LAMINATE		
ix)	BIO- TOILET			OMAX		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date					
		4040	NC	WGACCN	14129	21-07-2014					
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
12.2	Wheel & Axle Details:	PP Side				NPP Side					
	i.	Bogie No.	143256				143257				
	ii.	Frame No.	UBLS-4278				UBLS-4313				
	iii.	Axle No.	Y-6909		Y-6589		V-4181		3487		
	iv.	Wheel Diameter	916.00	916.00	912.00	912.00	916.00	916.00	915.00	915.00	
	v.	Wheel Disc No.	05579/ 368	05709/ 251	02190/ 242	02498/ 255	06369/ 267	05750/ 256	05383/ 242	05513/24 8	
	vi.	R.B. Nos.	E-2576	E-2594	E2510	E2495	D-0973	D-0962	E-2376	E-2345	
	vii.	R.B. Make	NBC		NBC		NBC		NBC		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	Items Traceability:										
	i.	BRAKE CYLINDER (Make)					AJT				
	ii.	SECONDARY Shock Absorber (Make)					GABRIEL				
12.4	i.	Modification/ Trail (if any):					NIL				
	ii.	Deviations (if any):					NIL				