



ROLLING STOCK CERTIFICATE

Form No. :

QMF4254;
Version: 05

1.	SHELL No:	4013	DISPATCH DATE:			24.12.2014
2.	RAILWAY	NWR	Type:	WGSCN	Coach No.:	14242
3.	Booked to	SSE/C&W/JP				
4.	Tare Weight of Coach :	38.03				
5.	Carrying Capacity :	Seating:	72	Sleeping:	72	Luggage: NIL
6.	Shell Details: SE90017					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator		4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
ii)	Maximum length over Body		21337 ± 10			
iii)	Maximum length over Buffer		22297 ± 15			
iv)	Maximum width over Body		3245 ± 5			
v)	Maximum width over Flasher light		3402 +0/-5			
vi)	Minimum height above rail level to the lowest fitting		181.5			
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm	1104/1104	1104/1104		
viii)	Buffer/CBC (Make)		JLS			
ix)	Draw Gear (Make)		EMSON			
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
		TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
8.1	PAINT	PU PAINT	VIBGYOR	85/85		
8.2	APPLICATION OF PCN-123		SATISFACTORY			
8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORT		
ii.	SEAT & BERTH			SUKATA		
iii.	WATER TANKS			RUBCONE`		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			TAYAL		
vi.	WINDOWS			ABC, MECIDON		
vii.	LAV. DOORS			JR		
viii.	LP SHEET			NK		
ix)	BIO- TOILET			M K PRECISION		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4013	NW	SCN	14242	27-11-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141510				141512			
	ii.	Frame No.	ASR-663				ASR-575			
	iii.	Axle No.	Z-1386		A-4283		W-3169		A-019	
	iv.	Wheel Diameter	917.00	917.00	917.00	917.00	917.00	917.00	917.00	917.00
	v.	Wheel Disc No.	08740/ 276	08842/ 264	06938/ 371	06965/ 243	05959/ 217	08084/ 288	08808/ 216	08890/20 4
	vi.	R.B. Nos.	S434	V1771	V1748	V1574	S265	S273	V1562	V1745
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				GABRIEL, K/B				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



ROLLING STOCK CERTIFICATE

Form No. :

QMF4254;
Version: 05

1.	SHELL No:	4010	DISPATCH DATE:			24.12.2014
2.	RAILWAY	NWR	Type:	WGSCN	Coach No.:	14241
3.	Booked to	SSE/C&W/JP				
4.	Tare Weight of Coach :	38.03				
5.	Carrying Capacity :	Seating:	72	Sleeping:	72	Luggage: NIL
6.	Shell Details: SE90017					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		AUSTIN	85/85	
8.2	APPLICATION OF PCN-123		SATISFACTORY			
8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORT		
ii.	SEAT & BERTH			SUKATA		
iii.	WATER TANKS			RUBCONE`		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			TAYAL		
vi.	WINDOWS			AGF, ABC, MECIDON		
vii.	LAV. DOORS			JR		
viii.	LP SHEET			NK		
ix)	BIO- TOILET			M K PRECISION		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4010	NW	SCN	14241	5-12-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141548				141558			
	ii.	Frame No.	ASR-671				ASR-621			
	iii.	Axle No.	P-3819		M-7791		V-9052		Y-8586	
	iv.	Wheel Diameter	916.50	916.00	917.00	917.00	917.00	917.00	917.00	917.00
	v.	Wheel Disc No.	08886/278	08093/270	09033/384	07338/266	08890/205	08890/215	08067/285	07282/202
	vi.	R.B. Nos.	V1311	S-717	V1288	V1305	V1281	V1300	V1301	V1307
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT,PEW				
	ii.	SECONDARY Shock Absorber (Make)				KNORR BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. :

QMF4254;
Version: 05

1.	SHELL No:	4014	DISPATCH DATE:			24.12.2014
2.	RAILWAY	NWR	Type:	WGSCN	Coach No.:	14240
3.	Booked to	SSE/C&W/JP				
4.	Tare Weight of Coach :	38.03				
5.	Carrying Capacity :	Seating:	72	Sleeping:	72	Luggage: NIL
6.	Shell Details: SE90017					
6.1	Leading Dimensions;					
i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
ii)	Maximum length over Body			21337 ± 10		
iii)	Maximum length over Buffer			22297 ± 15		
iv)	Maximum width over Body			3245 ± 5		
v)	Maximum width over Flasher light			3402 +0/-5		
vi)	Minimum height above rail level to the lowest fitting			181.5		
vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
viii)	Buffer/CBC (Make)			JLS		
ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:					
	Description			Specified		
7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
		Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
		TYPE OF PAINT		MAKE	AVERAGE GLOSS VALUE	
8.1	PAINT	PU PAINT		VIBGYOR	85/85	
8.2	APPLICATION OF PCN-123		SATISFACTORY			
8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make		
i.	BRAKE EQUIPMENT			ESCORT		
ii.	SEAT & BERTH			SUKATA		
iii.	WATER TANKS			AMIT		
iv.	PVC			RESPONSIVE		
v.	FLOOR BOARD			TAYAL		
vi.	WINDOWS			AGF,ABC, MECIDON		
vii.	LAV. DOORS			JR		
viii.	LP SHEET			PUNJAB LAMINATE		
ix)	BIO- TOILET			DARSHAN		
10.	10.1	Modification/ Trial (if any):			NIL	
	10.2	Deviations (if any):			NIL	



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

12.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		4014	NW	SCN	14240	05-12-2014				
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
12.2	Wheel & Axle Details:	PP Side				NPP Side				
	i.	Bogie No.	141557				141556			
	ii.	Frame No.	UBLS-1202				ASR-611			
	iii.	Axle No.	Y-6311		U-8752		A-4667		RWF-91454	
	iv.	Wheel Diameter	917.00	917.00	917.00	917.00	917.00	917.00	917.00	917.00
	v.	Wheel Disc No.	08092/202	08070/287	08087/262	08882/253	07244/295	08067/266	07359/255	09027/205
	vi.	R.B. Nos.	V-1294	V-1306	V-1012	V-1291	V-1297	V-1293	V1295	V-1286
	vii.	R.B. Make	FAG		FAG		FAG		FAG	
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing							
12.3	Items Traceability:									
	i.	BRAKE CYLINDER (Make)				AJT				
	ii.	SECONDARY Shock Absorber (Make)				KNORR BREMSE				
12.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

SCN-4014



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. :

QMF4254;
Version: 05

1.	SHELL No:	4012	DISPATCH DATE:			27.12.2014	
2.	RAILWAY	NWR	Type:	WGSCN	Coach No.:	14244	
3.	Booked to	SSE/C&W/JP					
4.	Tare Weight of Coach :	38.03					
5.	Carrying Capacity :	Seating:	72	Sleeping:	72	Luggage:	NIL
6.	Shell Details: SE90017						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator	4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)				
	ii)	Maximum length over Body	21337 ± 10				
	iii)	Maximum length over Buffer	22297 ± 15				
	iv)	Maximum width over Body	3245 ± 5				
	v)	Maximum width over Flasher light	3402 +0/-5				
	vi)	Minimum height above rail level to the lowest fitting	181.5				
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm	1104/1104	1104/1104		
	viii)	Buffer/CBC (Make)	REPL				
	ix)	Draw Gear (Make)	EMSON				
7.	Air Brake Testing:						
		Description	Specified				
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC	Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)			
			Brake release time to reach .4 Kg/cm2	Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)			
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec	No brake application			
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec	Brakes "ON"			
	7.4	Passenger alarm by pulling chain	BP Blasts out, Brakes "ON"				
	7.5	Piston stroke for BMBC type coach only	19 +10/-0 mm (NAC)				
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	VIBGYOR	85/86		
	8.2	APPLICATION OF PCN-123	SATISFACTORY				
	8.3	INSUALTION	SATISFACTORY				
9.	Traceability of Furnishing Items:						
	i.	BRAKE EQUIPMENT	Make ESCORT				
	ii.	SEAT & BERTH	SUKATA				
	iii.	WATER TANKS	RAIL FAB				
	iv.	PVC	RESPONSIVE				
	v.	FLOOR BOARD ,UIC	TAYAL ,KRP				
	vi.	WINDOWS	ABC, MECIDON				
	vii.	LAV. DOORS	JR				
	viii.	LP SHEET	NA				
	ix)	BIO- TOILET	M K PRECISION				
10.	10.1	Modification/ Trial (if any):	NIL				
	10.2	Deviations (if any):	NIL				



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date		
		4012	NWR		WGSCN		14244		04-12-2014		
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
12.2	Wheel & Axle Details:	PP Side					NPP Side				
	i.	Bogie No.	141544					141542			
	ii.	Frame No.	ASR-712					ASR-681			
	iii.	Axle No.	4893		U-7094		A-3895		U-6945		
	iv.	Wheel Diameter	916.00	916.50	917.00	917.00	916.00	916.00	917.00	917.00	
	v.	Wheel Disc No.	08943/ 268	08937/ 246	08963/ 279	07163/ 228	09139/ 266	08891/ 273	08891/ 257	09035/23 8	
	vi.	R.B. Nos.	V-1232	V-1125	V-1116	V-1118	V-1043	V-1186	V-1198	V-1179	
	vii.	R.B. Make	FAG		FAG		FAG		FAG		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	Items Traceability:										
	i.	BRAKE CYLINDER (Make)					AJT				
	ii.	SECONDARY Shock Absorber (Make)					KNORR BREMSE				
12.4	i.	Modification/ Trail (if any):					NIL				
	ii.	Deviations (if any):					NIL				

SCN-4012



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. :

QMF4254;
Version: 05

1.	SHELL No:	4015	DISPATCH DATE:			29.12.2014
2.	RAILWAY	NWR	Type:	WGSCN	Coach No.:	14243
3.	Booked to	SSE/C&W/JP				
4.	Tare Weight of Coach :	38.03				
5.	Carrying Capacity :	Seating:	72	Sleeping:	72	Luggage: NIL
6.	Shell Details: SE90017					
	6.1	Leading Dimensions;				
	i)	Maximum height above rail to top of Roof ventilator	4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)			
	ii)	Maximum length over Body	21337 ± 10			
	iii)	Maximum length over Buffer	22297 ± 15			
	iv)	Maximum width over Body	3245 ± 5			
	v)	Maximum width over Flasher light	3402 +0/-5			
	vi)	Minimum height above rail level to the lowest fitting	181.5			
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm	1104/1103	1104/1104	
	viii)	Buffer/CBC (Make)	JLS			
	ix)	Draw Gear (Make)	EMSON			
7.	Air Brake Testing:					
		Description	Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm2 of BC	Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
			Brake release time to reach .4 Kg/cm2	Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm2 n 60 sec	No brake application		
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm2 in 6 sec	Brakes "ON"		
	7.4	Passenger alarm by pulling chain	BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only	19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:					
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE	
	8.1	PAINT	PU PAINT	VIBGYOR	85/86	
	8.2	APPLICATION OF PCN-123	SATISFACTORY			
	8.3	INSUALTION	SATISFACTORY			
9.	Traceability of Furnishing Items:					
	i.	BRAKE EQUIPMENT	Make ESCORT			
	ii.	SEAT & BERTH	SUKATA			
	iii.	WATER TANKS	RAIL FAB			
	iv.	PVC	RESPONSIVE			
	v.	FLOOR BOARD ,UIC	TAYAL ,KRP			
	vi.	WINDOWS	ABC, MECIDON			
	vii.	LAV. DOORS	JR			
	viii.	LP SHEET	NA			
	ix)	BIO- TOILET	M K PRECISION			
10.	10.1	Modification/ Trial (if any):	NIL			
	10.2	Deviations (if any):	NIL			



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 2 of 3

12.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date		
		4015	NWR		WGSCN		14243		01-12-2014		
12.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
12.2	Wheel & Axle Details:	PP Side					NPP Side				
	i.	Bogie No.	141528					141523			
	ii.	Frame No.	ASR-373					ASR-647			
	iii.	Axle No.	V-9226		9262		0600		5185		
	iv.	Wheel Diameter	917.00	917.00	917.00	917.00	918.00	918.00	918.00	918.00	
	v.	Wheel Disc No.	07333/ 256	05858/ 237	08998/ 212	09119/ 228	07174/ 243	06857/ 223	09108/ 386	09073/25 2	
	vi.	R.B. Nos.	S-47	S-193	S-206	S-204	T-2569	V-1228	S-375	V-1205	
	vii.	R.B. Make	FAG		FAG		FAG		FAG		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
12.3	Items Traceability:										
	i.	BRAKE CYLINDER (Make)					AJT				
	ii.	SECONDARY Shock Absorber (Make)					KNORR BREMSE				
12.4	i.	Modification/ Trail (if any):					NIL				
	ii.	Deviations (if any):					NIL				

SCN-4015