



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	5079	DISPATCH DATE:				17.11.2015
2.	RAILWAY	WR	Type:	GSLRD	Coach No.:	15710	
3.	Booked to			SSE/C&W/OKHA			
4.	Tare Weight of Coach :			37.10 T			
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T	
6.	Shell Details: (SG-90004 alt 'b')						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
	ii)	Maximum length over Body			21337 ± 10		
	iii)	Maximum length over Buffer			22297 ± 15		
	iv)	Maximum width over Body			3245 ± 5		
	v)	Maximum width over Flasher light			3402 +0/-5		
	vi)	Minimum height above rail level to the lowest fitting			200 mm		
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
	viii)	Buffer/CBC (Make)			HEPL		
	ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:						
	Description			Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
			Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	VIBGYOR	85/86		
	8.2	APPLICATION OF PCN-123		SATISFACTORY			
	8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
	i.	BRAKE EQUIPMENT		ESCORTS			
	ii.	SEAT & BERTH		FLEXO FOAMS			
	iii.	WATER TANKS		AMIT			
	iv.	PVC		RESPONSIVE			
	v.	FLOOR BOARD		TAYAL			
	vi.	UIC VESTIBULE		NA			
	vii.	LAV. DOORS		GANDHI & ANKUR			
	viii.	LP SHEET		NK			
	ix)	BIO- TOILET		RAIL FAB			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

11.	Bogie Details:	Shell No.		Railway		Type		Coach No.		Dispatch Date	
		5079		WR		GSLRD		15710		06-11-2015	
11.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
11.2	Wheel & Axle Details:		PP Side				NPP Side				
	i.	Bogie No.	151436				151435				
	ii.	Frame No.	UBLS-1695				ASR-777				
	iii.	Axle No.	A-3564		N-8054		J-8849		J-8707		
	iv.	Wheel Diameter	916.50	916.00	916.00	916.00	916.00	916.00	916.00	916.00	
	v.	Wheel Disc No.	08992/ 259	08103/ 226	13836/ 393	06357/ 260	15379/ 316	08061/ 263	06937/ 387	13984/22 3	
	vi.	R.B. Nos.	F1196	F1241	F1199	F1213	G1555	F0938	G1535	G1547	
	vii.	R.B. Make	NBC		NBC		NBC		NBC		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
11.3	<u>Items Traceability:</u>					PP SIDE			NPP SIDE		
	i.	BRAKE CYLINDER Make & NO.				PEW-072,145			PEW-038,184		
	ii.	SECONDARY Shock Absorber Make &NO.				ESCORTS-8547,8721			ESCORTS-8598,8895		
11.4	i.	Modification/ Trail (if any):				NIL					
	ii.	Deviations (if any):				NIL					

GSLRD-5079



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	5101	DISPATCH DATE:				30.12.2015
2.	RAILWAY	WR	Type:	GSLRD	Coach No.:	15715	
3.	Booked to		SSE/C&W/OKHA				
4.	Tare Weight of Coach :		37.10 T				
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T	
6.	Shell Details: (SG-90004 alt 'b')						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
	ii)	Maximum length over Body			21337 ± 10		
	iii)	Maximum length over Buffer			22297 ± 15		
	iv)	Maximum width over Body			3245 ± 5		
	v)	Maximum width over Flasher light			3402 +0/-5		
	vi)	Minimum height above rail level to the lowest fitting			200 mm		
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
	viii)	Buffer/CBC (Make)			ATUL		
	ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:						
	Description			Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
			Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	VIBGYOR	85/86		
	8.2	APPLICATION OF PCN-123		SATISFACTORY			
	8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
	i.	BRAKE EQUIPMENT		ESCORTS			
	ii.	SEAT & BERTH		AAR KAY FOAMS			
	iii.	WATER TANKS		RUBICONE, AMIT			
	iv.	PVC		RESPONSIVE			
	v.	FLOOR BOARD		TAYAL			
	vi.	UIC VESTIBULE		NA			
	vii.	LAV. DOORS		TWPL & ANKUR			
	viii.	LP SHEET		NA			
	ix)	BIO- TOILET		OMAX			
10.	10.1	Modification/ Trial (if any):		NIL			
	10.2	Deviations (if any):		NIL			



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

11.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date			
		5101	WR	GSLRD	15715	18-12-2015			
11.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'								
11.2	Wheel & Axle Details:	PP Side				NPP Side			
	i. Bogie No.	151644				151650			
	ii. Frame No.	ASR-910				ASR-779			
	iii. Axle No.	K-5225		K-5619		11496		J-3025	
	iv. Wheel Diameter	916.00	916.00	915.00	915.00	917.00	917.00	916.00	916.00
	v. Wheel Disc No.	09123/ 205	16431/ 329	06964/ 236	16350/ 390	16679/ 313	16677/ 226	16409/ 315	16417/27 2
	vi. R.B. Nos.	Q2651	Q2741	Q2738	S0531	S1092	S1087	Q2751	Q2739
	vii. R.B. Make	FAG		FAG		FAG		FAG	
viii . R.B. Type	Direct Mounted Spherical Roller Bearing								
11.3	<u>Items Traceability:</u>				PP SIDE		NPP SIDE		
	i.	BRAKE CYLINDER Make & NO.			PEW-E11703,E11474			ATOOL-839,963	
	ii.	SECONDARY Shock Absorber Make &NO.			ESCORTS-0491,9075			ESCORTS-0463,0372	
11.4	i.	Modification/ Trail (if any):			NIL				
	ii.	Deviations (if any):			NIL				

GSLRD-5101



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	5100	DISPATCH DATE:				29.12.2015
2.	RAILWAY	WR	Type:	GSLRD	Coach No.:	15713	
3.	Booked to			SSE/C&W/OKHA			
4.	Tare Weight of Coach :			37.10 T			
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T	
6.	Shell Details: (SG-90004 alt 'b')						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
	ii)	Maximum length over Body			21337 ± 10		
	iii)	Maximum length over Buffer			22297 ± 15		
	iv)	Maximum width over Body			3245 ± 5		
	v)	Maximum width over Flasher light			3402 +0/-5		
	vi)	Minimum height above rail level to the lowest fitting			200 mm		
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
	viii)	Buffer/CBC (Make)			HEPL		
	ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:						
	Description			Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
			Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	VIBGYOR	86/87		
	8.2	APPLICATION OF PCN-123		SATISFACTORY			
	8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
	i.	BRAKE EQUIPMENT		ESCORTS			
	ii.	SEAT & BERTH		AAR KAY FOAMS			
	iii.	WATER TANKS		AMIT			
	iv.	PVC		RESPONSIVE			
	v.	FLOOR BOARD		TAYAL			
	vi.	UIC VESTIBULE		NA			
	vii.	LAV. DOORS		TWPL, DHINJAN & ANKUR			
	viii.	LP SHEET		PL			
	ix)	BIO- TOILET		RAIL FAB			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

11.	Bogie Details:	Shell No.	Railway		Type	Coach No.		Dispatch Date			
		5100	WR		GSLRD	15713		17-12-2015			
11.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
11.2	Wheel & Axle Details:	PP Side				NPP Side					
	i.	Bogie No.	151634				151635				
	ii.	Frame No.	ASR-908				ASR-902				
	iii.	Axle No.	J-2807		C-1202		H-0074		K-4498		
	iv.	Wheel Diameter	916.00	916.00	916.00	916.00	916.00	916.00	916.00	916.00	
	v.	Wheel Disc No.	13876/244	10318/217	11982/379	10389/221	06278/212	16379/248	16192/235	16438/316	
	vi.	R.B. Nos.	Q2752	Q2670	Q2658	Q2733	Q2657	S1151	Q2669	S1171	
	vii.	R.B. Make	FAG		FAG		FAG		FAG		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
11.3	<u>Items Traceability:</u>				PP SIDE		NPP SIDE				
	i.	BRAKE CYLINDER Make & NO.				PEW-E11639,E11622		PEW-E11713,E11716			
	ii.	SECONDARY Shock Absorber Make &NO.				ESCORTS-9107,0311		ESCORTS-9057,8846			
11.4	i.	Modification/ Trail (if any):				NIL					
	ii.	Deviations (if any):				NIL					

GSLRD-5100



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	5103	DISPATCH DATE:				04.01.2016
2.	RAILWAY	WR	Type:	GSLRD	Coach No.:	15717	
3.	Booked to		SSE/C&W/OKHA				
4.	Tare Weight of Coach :		37.10 T				
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T	
6.	Shell Details: (SG-90004 alt 'b')						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
	ii)	Maximum length over Body			21337 ± 10		
	iii)	Maximum length over Buffer			22297 ± 15		
	iv)	Maximum width over Body			3245 ± 5		
	v)	Maximum width over Flasher light			3402 +0/-5		
	vi)	Minimum height above rail level to the lowest fitting			200 mm		
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
	viii)	Buffer/CBC (Make)			ATUL		
	ix)	Draw Gear (Make)			CFPL		
7.	Air Brake Testing:						
	Description			Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
			Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	VIBGYOR	86/87		
	8.2	APPLICATION OF PCN-123		SATISFACTORY			
	8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
	i.	BRAKE EQUIPMENT		ESCORTS			
	ii.	SEAT & BERTH		AAR KAY FOAMS			
	iii.	WATER TANKS		RUBICONE, AMIT			
	iv.	PVC		RESPONSIVE			
	v.	FLOOR BOARD		TAYAL			
	vi.	UIC VESTIBULE		NA			
	vii.	LAV. DOORS		TWPL, DHINJAN & ANKUR			
	viii.	LP SHEET		PL			
	ix)	BIO- TOILET		RAIL FAB			
10.	10.1	Modification/ Trial (if any):		NIL			
	10.2	Deviations (if any):		NIL			



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

11.	Bogie Details:	Shell No.	Railway		Type		Coach No.		Dispatch Date
		5103	WR		GSLRD		15717		28-12-2015
11.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'								
11.2	Wheel & Axle Details:	PP Side				NPP Side			
	i. Bogie No.	151681				151686			
	ii. Frame No.	UBLS-1791				UBLS-1781			
	iii. Axle No.	H-0184		J-3307		06207		6381	
	iv. Wheel Diameter	916.00	916.00	916.00	916.00	916.00	916.00	915.00	915.00
	v. Wheel Disc No.	47502/ 09658	47660/ 09724	47581/ 09658	49293/ 10177	50114/ 10518	49632/ 10345	50148/ 10518	50116/10 518
	vi. R.B. Nos.	V1370	V1369	V1399	V1349	V1255	V1212	V1151	V1143
	vii. R.B. Make	FAG		FAG		FAG		FAG	
	viii . R.B. Type	Direct Mounted Spherical Roller Bearing							
11.3	<u>Items Traceability:</u>				PP SIDE		NPP SIDE		
	i.	BRAKE CYLINDER Make & NO.			ASSOC-916,028		ASSOC-987,907		
	ii.	SECONDARY Shock Absorber Make &NO.			ESCORTS-181,189		ESCORTS-0253,0154		
11.4	i.	Modification/ Trail (if any):			NIL				
	ii.	Deviations (if any):			NIL				

GSLRD-5103



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	5102	DISPATCH DATE:				08.01.2016
2.	RAILWAY	WR	Type:	GSLRD	Coach No.:	15716	
3.	Booked to			SSE/C&W/OKHA			
4.	Tare Weight of Coach :			37.10 T			
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T	
6.	Shell Details: (SG-90004 alt 'b')						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
	ii)	Maximum length over Body			21337 ± 10		
	iii)	Maximum length over Buffer			22297 ± 15		
	iv)	Maximum width over Body			3245 ± 5		
	v)	Maximum width over Flasher light			3402 +0/-5		
	vi)	Minimum height above rail level to the lowest fitting			200 mm		
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
	viii)	Buffer/CBC (Make)			HEPL		
	ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:						
	Description			Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
			Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	VIBGYOR	85/87		
	8.2	APPLICATION OF PCN-123		SATISFACTORY			
	8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
	i.	BRAKE EQUIPMENT		ESCORTS			
	ii.	SEAT & BERTH		AAR KAY FOAMS			
	iii.	WATER TANKS		RUBICONE, AMIT			
	iv.	PVC		RESPONSIVE			
	v.	FLOOR BOARD		TAYAL			
	vi.	UIC VESTIBULE		NA			
	vii.	LAV. DOORS		TWPL, DHINJAN & ANKUR			
	viii.	LP SHEET		PL			
	ix)	BIO- TOILET		RAIL FAB			
10.	10.1	Modification/ Trial (if any):			NIL		
	10.2	Deviations (if any):			NIL		



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

11.	Bogie Details:	Shell No.		Railway		Type		Coach No.		Dispatch Date	
		5102		WR		GSLRD		15716		22-12-2015	
11.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'										
11.2	Wheel & Axle Details:	PP Side					NPP Side				
	i.	Bogie No.	151664					151651			
	ii.	Frame No.	ASR-848					ASR-901			
	iii.	Axle No.	K-7052		K-4267		J-3050		J-8839		
	iv.	Wheel Diameter	916.00	916.00	916.00	916.00	916.00	916.00	915.50	915.50	
	v.	Wheel Disc No.	16771/ 240	16228/ 310	16245/ 397	16724/ 237	16433/ 322	16282/ 315	16242/ 333	16770/39 1	
	vi.	R.B. Nos.	Q-2759	Q2779	U2719	U2717	U2237	U2614	Q2782	Q2768	
	vii.	R.B. Make	FAG		FAG		FAG		FAG		
	viii.	R.B. Type	Direct Mounted Spherical Roller Bearing								
11.3	Items Traceability:					PP SIDE			NPP SIDE		
	i.	BRAKE CYLINDER Make & NO.				ATOOL-966,952			ATOOL-925,907		
	ii.	SECONDARY Shock Absorber Make &NO.				ESCORTS-0162,0129			ESCORTS-0141,0241		
11.4	i.	Modification/ Trail (if any):				NIL					
	ii.	Deviations (if any):				NIL					

GSLRD-5102



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	5104	DISPATCH DATE:				08.01.2016
2.	RAILWAY	WR	Type:	GSLRD	Coach No.:	15718	
3.	Booked to		SSE/C&W/OKHA				
4.	Tare Weight of Coach :		37.10 T				
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T	
6.	Shell Details: (SG-90004 alt 'b')						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
	ii)	Maximum length over Body			21337 ± 10		
	iii)	Maximum length over Buffer			22297 ± 15		
	iv)	Maximum width over Body			3245 ± 5		
	v)	Maximum width over Flasher light			3402 +0/-5		
	vi)	Minimum height above rail level to the lowest fitting			200 mm		
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
	viii)	Buffer/CBC (Make)			ATUL		
	ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:						
	Description			Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
			Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	VIBGYOR	86/87		
	8.2	APPLICATION OF PCN-123		SATISFACTORY			
	8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
	i.	BRAKE EQUIPMENT		ESCORTS			
	ii.	SEAT & BERTH		AAR KAY FOAMS			
	iii.	WATER TANKS		RUBICONE			
	iv.	PVC		RESPONSIVE			
	v.	FLOOR BOARD		TAYAL			
	vi.	UIC VESTIBULE		NA			
	vii.	LAV. DOORS		TWPL, DHINJAN & ANKUR			
	viii.	LP SHEET		PL			
	ix)	BIO- TOILET		RAIL FAB			
10.	10.1	Modification/ Trial (if any):		NIL			
	10.2	Deviations (if any):		NIL			



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

11.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date			
		5104	WR	GSLRD	15718	29-12-2015			
11.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'								
11.2	Wheel & Axle Details:	PP Side				NPP Side			
	i. Bogie No.	151683				151682			
	ii. Frame No.	UBLS-1742				UBLS-1806			
	iii. Axle No.	K-8319		J-2608		G-9967		G-9826	
	iv. Wheel Diameter	917.00	917.00	916.00	916.00	916.00	916.00	916.00	916.00
	v. Wheel Disc No.	15371/266	09100/270	16414/327	16487/310	16768/315	16740/242	16422/323	16542/279
	vi. R.B. Nos.	S1057	S1056	Q0749	Q0751	S1162	S1169	V1193	V1263
	vii. R.B. Make	FAG		FAG		FAG		FAG	
viii. R.B. Type	Direct Mounted Spherical Roller Bearing								
11.3	<u>Items Traceability:</u>				PP SIDE		NPP SIDE		
	i.	BRAKE CYLINDER Make & NO.			ATOOLS-855,834		ATOOLS-912,875		
	ii.	SECONDARY Shock Absorber Make &NO.			ESCORTS-0198,0186		ESCORTS-0322,0173		
11.4	i.	Modification/ Trail (if any):			NIL				
	ii.	Deviations (if any):			NIL				

GSLRD-5104



रेल डिब्बा कारखाना, कपूरथला
Rail Coach Factory , Kapurthala

Page 1 of 3

ROLLING STOCK CERTIFICATE

Form No. : QMF4254; Version: 05

1.	SHELL No:	5098	DISPATCH DATE:				26.12.2015
2.	RAILWAY	WR	Type:	GSLRD	Coach No.:	15714	
3.	Booked to		SSE/C&W/OKHA				
4.	Tare Weight of Coach :		37.10 T				
5.	Carrying Capacity :	Seating:	20	Sleeping:	4	Luggage: 8T	
6.	Shell Details: (SG-90004 alt 'b')						
	6.1	Leading Dimensions;					
	i)	Maximum height above rail to top of Roof ventilator			4100 ± 5 (for NAC) 4250 +0/-5 (for WGACCN only)		
	ii)	Maximum length over Body			21337 ± 10		
	iii)	Maximum length over Buffer			22297 ± 15		
	iv)	Maximum width over Body			3245 ± 5		
	v)	Maximum width over Flasher light			3402 +0/-5		
	vi)	Minimum height above rail level to the lowest fitting			200 mm		
	vii)	Buffer/CBC Height	Specified : 1104 +0 /-10 mm		1104/1104	1104/1104	
	viii)	Buffer/CBC (Make)			HEPL		
	ix)	Draw Gear (Make)			EMSON		
7.	Air Brake Testing:						
	Description			Specified			
	7.1	Emergency Application	Time for 0 to 3.6 Kg/cm ² of BC		Less than 05 Sec (for BMBC type) 3 to 5 Sec (for Non BMBC type)		
			Brake release time to reach .4 Kg/cm ²		Less than 20 Sec (for BMBC type) 15 to 20 Sec (for Non BMBC type)		
	7.2	Insensitivity	BP dipped @ 0.30 Kg/cm ² n 60 sec		No brake application		
	7.3	Sensitivity	BP dipped @ 0.60 Kg/cm ² in 6 sec		Brakes "ON"		
	7.4	Passenger alarm by pulling chain		BP Blasts out, Brakes "ON"			
	7.5	Piston stroke for BMBC type coach only		19 +10/-0 mm (NAC)			
8.	PAINTING DEATAILS:						
			TYPE OF PAINT	MAKE	AVERAGE GLOSS VALUE		
	8.1	PAINT	PU PAINT	ADVANCE	85/86		
	8.2	APPLICATION OF PCN-123		SATISFACTORY			
	8.3	INSUALTION		SATISFACTORY			
9.	Traceability of Furnishing Items:			Make			
	i.	BRAKE EQUIPMENT		ESCORTS			
	ii.	SEAT & BERTH		AAR KAY FOAMS`			
	iii.	WATER TANKS		RUBICONE, AMIT			
	iv.	PVC		RESPONSIVE			
	v.	FLOOR BOARD		TAYAL			
	vi.	UIC VESTIBULE		NA			
	vii.	LAV. DOORS		TWPL, DHINJAN & ANKUR			
	viii.	LP SHEET		NA			
	ix)	BIO- TOILET		RAIL FAB			
10.	10.1	Modification/ Trial (if any):		NIL			
	10.2	Deviations (if any):		NIL			



रेल डिब्बा कारखाना, कपूरथला

Rail Coach Factory , Kapurthala

Page 2 of 3

11.	Bogie Details:	Shell No.	Railway	Type	Coach No.	Dispatch Date				
		5098	WR	GSLRD	15714	15-12-2015				
11.1	BOGIE GENERAL ARRANGEMENT DRAWING NO.: CC00002 Alt 'a'									
11.2	Wheel & Axle Details:	PP Side				NPP Side				
	i. Bogie No.	151618				151619				
	ii. Frame No.	ASR-900				ASR-887				
	iii. Axle No.	K-8119		K-4733		J-8904		K-8877		
	iv. Wheel Diameter	915.00	915.00	916.00	916.00	916.00	916.00	915.50	915.00	
	v. Wheel Disc No.	16437/244	16472/393	13878/397	15353/383	16610/242	16434/242	16535/253	06972/274	
	vi. R.B. Nos.	U2262	U2086	S0734	S0749	U3123	U3085	S0786	S0718	
	vii. R.B. Make	FAG		FAG		FAG		FAG		
viii. R.B. Type	Direct Mounted Spherical Roller Bearing									
11.3	<u>Items Traceability:</u>				PP SIDE		NPP SIDE			
	i.	BRAKE CYLINDER Make & NO.				PEW-11762,11632		PEW-11685,9972		
	ii.	SECONDARY Shock Absorber Make &NO.				ESCORTS-9108,542		ESCORTS-8746,328		
11.4	i.	Modification/ Trail (if any):				NIL				
	ii.	Deviations (if any):				NIL				

GSLRD-5098